Submit 3 Copies to Appropriate District Office

State of New Mexico Energy, Minerals and Natural Resources Department

11

DISTRICT

CONDITIONS OF APPROVAL, IF ANY:

OIL CONSERVATION DIVISION

151	Form C-
W	Revised
T.	

P.O. Box 1980, Hobbs, NM 88240	2040 Pacheco St.			WELL API NO.		
DISTRICT II Santa Fe, NM 87505			30-005-63190			
P.O. Drawer DD, Artesia, NM 88210		sIndicate Type of Lease				
DISTRICT III				STATE	FEE	
1000 Rio Brazos Rd., Aztec, NM 87410			oState Oil & Gas Lease No.			
SUNDRY NOTI	CES AND DEDORTS ON	VAE'	16	etaan keroloa (Aginto) ala Petoto. Ta	No. of Carlot Projection	
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A		rLease Name or Unit Agreement Name				
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		Twin Lakes San Andres Unit				
1Type of Well:	101) FOR SUCH PROPUSALS.	.,				
OIL GAS WELL OTHER						
3Name of Operator HANAGAN PETROLEUM CORPO	RATION			sWell No. 329		
3Address of Operator		⊌Pool name or Wildcat				
P.O. BOX 1737 - ROSWELL, NM	88202-1737			Twin Lakes San Andres (Associated)		
4Well Location Unit Letter	Feet From The NORTH	4	Line and 2310	Feet From The	WEST	Line
6 Section 9s					CHAVEC	
	Township 290		RKB.RT.GR.etc)	NMPM	CHAVES	County
	3991' KB					
11 Check Ap	propriate Box to Indicat	te Na	ture of Notice, Rep	ort, or Other i	Data	
NOTICE OF INT	ENTION TO:		SUBS	SEQUENT RE	EPORT OF:	
PERFORM REMEDIAL WORK	PLUG AND ABANDON		REMEDIAL WORK		ALTERING CASI	NG
TEMPORARILY ABANDON	CHANGE PLANS		COMMENCE DRILLING OPNS. PLUG AND ANBANDONMENT			
PULL OR ALTER CASING			CASING TEST AND CEMENT JOB			
OTHER:			OTHER:			
12Describe Proposed or Completed Operations work) SEE RULE 1103.	(Clearly state all pertinent details, a	ind give	pertinent dates, including est	imated date of starting	any proposed	
11/29/98 - MIRU United Drilling Co.	Rig #10 - drill 12.25" hole to	112' w	v/air - run 3jts 8.625" 24	#/ft casing to TD	- RU Roswell Re	eady Mix &
11/29/98 - MIRU United Drilling Co. Rig #10 - drill 12.25" hole to 112' w/air - run 3jts 8.625" 24#/ft casing to TD - RU Roswell Ready Mix & cement w/3yds Redi-Mix to surface - RD United Rig #10						
12/7/98 - MIRU United Drilling Co. Rig #4 - drill 7.875" hole to 2855'						
12/11/98 - TD 7.875" hole @ 2855' - Run 65jts of 5.5", 15.50#/ft J55 casing w/shoe @ 2849' (KB) -RU Halliburton & cement w/600sx Interfill "C" lead cement (weight=11.5, yield=2.71), tailed in w/300sx 50/50 Premium Plus Poz cement w/5#/sk salt & 0.6% Halad 322(weight=13.95, yield=1.39), circulate 200sx cement to pits - Release rig						
3456789 ₇₀₇₇						
			12	′ . ′′		
			**		51677	
I hereby certify that the information above is true endocuments to the head of the lead of						
I hereby certify that the information above is true and complete to the best of my knowledge and belief. SIGNATURE TITLE President DATE 12-14-98						
	1 0	''''		\$252224	UATE _12-14-	-90
TYPE OR PRINT NAME Michael G. Hanag					TELEPHONE NO. 62	3-5053
(This space for State Use)						
	SIGNED BY TIM W. GU II SUPERVISOR	***	15		/2	- 73 -98