Submit 3 Copies to Appropriate **District Office** 

CONDITIONS OF APPROVAL, IF ANY:

## State of New Mexico Energy, Minerals and Natural Resources Department

Form C-103 Revised 1-1-89

DISTRICT | P.O. Box 1980, Hobbs, NM 88240 OIL CONSERVATION DIVISION WELL API NO. 2040 Pacheco St. 30-005-63191 Santa Fe, NM 87505 DISTRICT II P.O. Drawer DD, Artesia, NM 88210 123456 sIndicate Type of Lease FEE X STATE «State Oil & Gas Lease No. 1000 Rio Brazos Rd., Aztec, NM 87410 SUNDRY NOTICES AND REPORTS ON WELL'S (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DESPENDED USE BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.) 7Lease Name or Unit Agreement Name Twin Lakes San Andres Unit Type of Well: GAS WELL 🛛 OTHER \*Name of Operator
HANAGAN PETROLEUM CORPORATION «Well No. 302 Address of Operator Pool name or Wildcat P.O. BOX 1737 - ROSWELL, NM - 88202-1737 Twin Lakes San Andres (Associated) **-Well Location** Unit Letter O : 950 SOUTH \_ Feet From The \_ 2310 Line and EAST Feet From The Line 25 88 Section Township CHAVES County 10Elevation (Show whether DF, RKB, RT, GR, etc.) 3933'kb Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PLUG AND ABANDON PERFORM REMEDIAL WORK REMEDIAL WORK **ALTERING CASING** TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ANBANDONMENT **PULL OR ALTER CASING** CASING TEST AND CEMENT JOB X OTHER: OTHER: 12Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1/18/99 - MIRU United Drilling Co. Rig #10 - drill 12.25" hole to 112' w/air - run 3jts 8.625" 24#/ft casing to TD - RU Valley Concrete & cement w/3yds Redi-Mix to surface - RD Rig #10

1/23/99 - TD 7.875" hole @ 2700' - Run 65jts of 5.5", 15.50#/ft 8rd J55 casing w/shoe @ 2695' (KB) -RU BJ Services & cement w/765sx 50% "C"/50% Poz w/5#-sk salt + 10% bentonite lead cement(weight=11.80#/gl / yield = 2.39), tailed in w/200sx Class "C" cement (weight=14.80#/gl / yield=1.32), circulate 167sx cement to pits - Release rig

I hereby certify that the information above is true and opmplete to the best of my knowledge and belief.		
SIGNATURE ///	TITLE President	DATE 01-29-99
TYPE OR PRINT NAME Michael G. Hanagan		TELEPHONE NO. 623-5053
(This space for State Use)	P	
ORIGINAL SIGNED BY TIM W. GUM APPROVED BY DISTRICT II SUPERVISOR	TITLE	DATE 2-5-99