

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

2040 Pacheco St.  
Santa Fe, NM 87505

WELL API NO.  
30-005-63193

Indicate Type of Lease  
STATE ☐ FEE ☒

State Oil & Gas Lease No.

Lease Name or Unit Agreement Name  
Twin Lakes San Andres Unit

Well No.  
333

Pool name or Wildcat  
Twin Lakes San Andres (Associated)

Elevation (Show whether DF, RKB, RT, GR, etc.)  
3944' KB

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

Type of Well:  
OIL ☒ GAS ☐ OTHER ☐

Name of Operator  
HANAGAN PETROLEUM CORPORATION

Address of Operator  
P.O. BOX 1737 - ROSWELL, NM - 88202-1737

Well Location  
Unit Letter J : 1670 Feet From The South Line and 1650 Feet From The East Line

6 Section 9s Township 29e Range NMPM CHAVES County

11

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐  
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐  
CASING TEST AND CEMENT JOB ☒  
OTHER: ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

11/29/98 - MIRU United Drilling Co. Rig #10 - drill 12.25" hole to 118' w/air - run 3jts 8.625" 24#/ft casing to TD - RU Roswell Ready Mix & cement w/3yds Redi-Mix to surface - RD United Rig #10

12/16/98 - MIRU United Drilling Co. Rig #4 - drill 7.875" hole to 2818'

12/20/98 - TD 7.875" hole @ 2830' - Run 64jts of 5.5", 15.50#/ft J55 casing w/shoe @ 2816' (KB) -RU Halliburton & cement w/600sx Interfill "C" lead cement (weight=11.5, yield=2.71), tailed in w/300sx 50/50 Premium Plus Poz cement w/5#/sk salt & 0.6% Halad 322(weight=13.95, yield=1.39), plug down @ 3:30pm, circulate 145sx cement to pits - Release rig

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Michael G. Hanagan TITLE President DATE 12-28-98

TYPE OR PRINT NAME Michael G. Hanagan TELEPHONE NO. 623-5053

(This space for State Use)

APPROVED BY Jim W. Green TITLE District Supervisor DATE 1-6-99

CONDITIONS OF APPROVAL, IF ANY: