

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

IL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.	30-005-632023
5. Indicate Type of Lease	STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.	
7. Lease Name or Unit Agreement Name	Presler Lake
8. Well No.	#7
9. Pool name or Wildcat	Many Gates SA

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	2. Name of Operator Hanson Operating Company, Inc.
3. Address of Operator P.O. Box 1515, Roswell, NM 88202-1515	4. Well Location Unit Letter G : 2310 Feet From The North Line and 1650 Feet From The East Line Section 12 Township 9S Range 29E NMPM Chaves County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 4058 GR	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☒
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 4-23-99 Ran 23 jts. of 8 5/8" 24# casing. Ran as follows:
1 guide shoe, 1.00'
1 shoe jt., 42.80'
1 insert float then 22 jts. totaling 949.09' landed & cemented at 1005' Cement as follows:
Lead cement 341 sxs Class C + 2% BWOC Calcium chloride, 80 sxs to pit. Plug down at 12pm
- 4-30-99 Ran 91 jts of 5 1/2" x 15.50 # casing. Ran as follows:
1 guide shoe .05', 1 shoe guide 42.50', 1 float collar 1.50'
then 90 jts of casing totaling 3413.71' landed & cemented at 3455.67'
Cemented as follows: pumped 12 bbls. of mud sweep then went to cement pumped 300 sxs of class H+5#. Plug down at 3:15am did not circulate any cement to surface.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Betsy Speer TITLE Production Analyst DATE 5-4-99
TYPE OR PRINT NAME Betsy Speer TELEPHONE NO. 505-622-7330

(This space for State Use)

APPROVED BY Leon W. Gunn TITLE District Supervisor DATE 5-11-99

CONDITIONS OF APPROVAL, IF ANY: