

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.
30-005-63206

5. Indicate Type of Lease
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.
LG-4334

7. Lease Name or Unit Agreement Name
Sparrow SP State

8. Well No.
7

9. Pool name or Wildcat
Pecos Slope Abo

10. Elevation (Show whether DP, RKB, RT, GR, etc.)
3899' GR

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☐ GAS WELL ☒ OTHER

2. Name of Operator
YATES PETROLEUM CORPORATION

3. Address of Operator
105 South 4th St., Artesia, NM 88210

4. Well Location
Unit Letter 0 : 660 Feet From The South Line and 1980 Feet From The East Line
Section 32 Township 6S Range 25E NMPM Chaves County

10. Elevation (Show whether DP, RKB, RT, GR, etc.)
3899' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐		CASING TEST AND CEMENT JOB ☐	
OTHER: ☐		OTHER: Intermediate casing & cement ☒	

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.
TD 1560'. Reached TD at 10:45 PM 11-6-99. Ran 35 joints of 8-5/8" 24# J-55 (1555.41') of casing set at 1560'. 1-Texas Pattern notched guide shoe set at 1554'. Float collar set at 1509'. Cemented with 100 sacks Thixset (yield 1.50, weight 14.1) and 360 sacks Halliburton Lite C, 1/4#/sack flocele, 5#/sack salt and 10#/sack gilsonite (yield 2.07, weight 12.5). Tailed in with 200 sacks Premium Plus and 2% CaCl2 (yield 1.34, weight 14.8). PD 7:00 AM 11-7-99. Bumped plug to 500 psi, OK. Circulated 165 sacks. WOC. Nipped up and tested to 1200 psi, OK. Drilled out at 9:45 AM 11-8-99. WOC 24 hours and 45 minutes. Reduced hole to 7-7/8". Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Operations Technician DATE Nov. 20, 1999
TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-147

(This space for State Use)

APPROVED BY Jim W. Gurn TITLE District Supervisor DATE 12-1-99
CONDITIONS OF APPROVAL, IF ANY: