

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.	30-005-63206
5. Indicate Type of Lease	STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.	LG-4334
7. Lease Name or Unit Agreement Name	Sparrow SP State
8. Well No.	7
9. Pool name or Wildcat	Pecos Slope Abo
10. Elevation (Show whether DF, RAB, RT, GR, etc.)	3899' GR

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☐

GAS
WELL ☒

OTHER

2. Name of Operator

YATES PETROLEUM CORPORATION

3. Address of Operator

105 South 4th St., Artesia, NM 88210

4. Well Location

Unit Letter 0 : 660 Feet From The South Line and 1980 Feet From The East Line

Section 32 Township 6S Range 25E NMPM Chaves County

10. Elevation (Show whether DF, RAB, RT, GR, etc.)

3899' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: Perforate & frac ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

12-10-99 - Rigged up wireline. TIH with casing guns and perforated 3617-3963' w/25 .38" holes as follows: 3617, 19, 21, 60 & 3662, 3693, 3711, 21, 32, 43, 78, 80, 82, 84, 3802, 04, 06, 08, 10, 12, 14, 3957, 59, 61 & 3963' (1 SPF - Abo). TOOH with casing guns and rigged down wireline. Prep to frac.

12-31-99 - Frac'd perforations 3617-3963' with 140000 gallons 65Q N2 foam and 244400# 16-30 mesh brown sand. Flowed well back. RIH with coiled tubing. Released well to production department.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Rusty Klein

TITLE

Operations Technician

DATE Jan. 11, 2000

TYPE OR PRINT NAME

Rusty Klein

TELEPHONE NO. 505/748-147

(This space for State Use)

ORIGINAL SIGNED BY TIM W. GUM
DISTRICT II SUPERVISOR

APPROVED BY

TITLE

DATE

1.11.00

CONDITIONS OF APPROVAL, IF ANY: