## State of New Mexico Form C-103 Submit 3 Copies 13 Appropriate District Office Energy, Minerals and Natural Resources Department Revised 1-1-89 OIL CONSERVATION DIVISION DISTRICT WELL API NO. P.O. Box 1980, Hobbs, NM 88240 P.O. Box 2088 30-005-63207 Santa Fe. New Mexico 87504-2088 DISTRICT II P.O. Drawer DD, Artesia, NM 88210 5. Indicate Type of Lease STATE FEE | 6. State Oil & Gas Lease No. 1000 Rio Brazos Rd., Aztec, NM 87410 LG-262 SUNDRY NOTICES AND REPORTS ON WELLS ( DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUS B. 7. Lease Name or Unit Agreement Name DIFFERENT RESERVOIR. USE "APPLICATION OF PERMIT (FORM C-101) FOR SUCH PROPOS 1. Type of Well: WELL WELL X Thunderhead TD State 2. Name of Operator 8. Well No. YATES PETROLEUM CORPORATION 3. Address of Operator 9. Pool name or Wildcat 105 South 4th St., Artesia, NM 88210 Undesignated 4. Well Location South Unit Letter K : 1980 Feet From The 1980 Feet From The West Line and Line Chaves 26E thip 8S Range 26E 10. Elevation (Show whether DF, RKB, RT, GR, etc.) Section Township **NMPM** County 3747' GR Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK **ALTERING CASING TEMPORARILY ABANDON CHANGE PLANS** COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT **PULL OR ALTER CASING** CASING TEST AND CEMENT JOB OTHER: Perforate & acidize OTHER: 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. 6-7-2000 - Rigged up wireline. TIH with logging tools and ran GR/CCL/CBL log. logging tools and rigged down wireline. 6-8-14-2000 - Waiting on completion unit. 6-15-2000 - Cleaned location. Welded on bell nipple. 6-16-2000 - Moved in and rigged up pulling unit. TIH with bit, scraper and tubing and

tagged up at 7056'. Pulled up to 6975'. Pickled tubing with 500 gallons of 20% HCL acid. Reversed out. Shut well in. 6-17-2000 - Rigged up wireline. TIH with 4" casing guns and perforated 6964-6974' w/40 .42" holes (4 SPF - Ordovician). TOOH with casing guns and rigged down wireline. TIH with packer with 1.87" on/off tool and tubing. Nippled down BOP. Set packer. Swabbed. Shut well in. 6-18-19-2000 - Swabbed. Shut well in. 6-20-2000 - Acidized perforations 6964-6974' with 250 gallons of 20% iron control HCL acid.

Flushed	wi)tl	1 2%	KCL.	Ļoaded	with	39 bt	ols.	Flowed	back 8	swabb	ed.	Shut	well in.		<del></del>
I hereby certify that	jhe info	mutipa	above is tos	and complete	o the best	of my know	wiedge and i	pelief.		C	ONTI	NUED	ON NEXT P	AGE:	
SIGNATURE	M	ste	09	Min	/			B Oper	ations	Techn	icia	n	_ DATE Aug.	31.	_2000_
TYPE OR PRINT NAI	n		Kleir			<del></del>							TELEPHONE NO.	505,	/748-1471

(This space for State Use)

DATE 8-31-05 SUPERVISOR, DISTRICT II .. TITLE APPROVED BY