

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.	30-005-63208
5. Indicate Type of Lease	STATE ☐ FEE ☒
6. State Oil & Gas Lease No.	
7. Lease Name or Unit Agreement Name	Getty PS 17
8. Well No.	2
9. Pool name or Wildcat	Pecos Slope Abo

10. Elevation (Show whether DF, RKB, RT, GR, etc.)	3625' GR
--	----------

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL ☐ GAS WELL ☒ OTHER ☐	2. Name of Operator YATES PETROLEUM CORPORATION
3. Address of Operator 105 South 4th St., Artesia, NM 88210	4. Well Location Unit Letter <u>I</u> : <u>1980</u> Feet From The <u>South</u> Line and <u>660</u> Feet From The <u>East</u> Line Section <u>17</u> Township <u>6S</u> Range <u>26E</u> NMMPM Chaves County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3625' GR	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK ☐	REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐	ALTERING CASING ☐
PULL OR ALTER CASING ☐	COMMENCE DRILLING OPNS. ☐
OTHER: ☐	PLUG AND ABANDONMENT ☐
	CASING TEST AND CEMENT JOB ☐
	OTHER: Production casing & cement ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 4230'. Reached TD at 4:30 PM 12-2-99. Ran 98 joints of 4-1/2" 10.5# J-55 (4203.48') of casing set at 4198'. Regular guide shoe set at 4198'. Float collar set at 4154'. Bottom marker set at 3483'. Cemented with 680 sacks Premium Plus with 1% CaCl2 and 1% Lone Seal 2000 (70-375 scf/bbl N2) (yield 2.57, weight 7.5-9.5). Tailed in with 365 sacks Super H Premium, 2.5#/sack salt, 5#/sack gilsonite, 4/10% LAP-1, 4/10% CFR3 (yield 1.64, weight 13.2). PD 7:00 PM 12-3-99. Bumped plug to 2000 psi for 1 minute. Circulate 5 sacks. WOC. Released rig at 11:00 PM 12-3-99. NOTE: Topped out bradenhead with 75 sacks Premium Plus with 2% CaCl2.

Waiting on completion unit.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Operations Technician DATE Dec. 13, 1999
TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-1471

(This space for State Use)

APPROVED BY Jim W. Green TITLE District Supervisor DATE 12-21-99
CONDITIONS OF APPROVAL, IF ANY: