N.M. Oil Cons. Parision 811 S. 1st Street Artesia, NM 88210-2834

Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR

FORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993 BUREAU OF LAND MANAGEMENT 5. Lease Designation and Serial No. NM-31944 SUNDRY NOTICES AND REPORTS ON WELLS 6. If Indian, Allottee or Tribe Name Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE 1. Type of Well Oil Well 8. Well Name and No. 2. Name of Operator L Reinauer RC Federal #2 YATES PETROLEUM CORPORATION (505) 748-1471)9. API Well No. 3. Address and Telephone No. 30-005-63216 105 South 4th St., Artesia, NM 88210 10. Field and Pool, or Exploratory Area 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) Pecos Slope Abo 1980' FNL & 1980' FEL of Section 20-T7S-R25E (Unit G, SWNE) 11. County or Parish, State Chaves Co., NM 12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Abandonment Change of Plans Recompletion X Subsequent Report **New Construction** Plugging Back Non-Routine Fracturing Casing Repair Final Abandonment Notice Water Shut-Off Altering Casing Conversion to Injection X Other Resume drlg, surface Dispose Water casing & cement 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* (Note Report results of multiple completion on Well Resumed drilling a 14-3/4" hole with rotary tools at 1:30 AM 1-7-2000. TD 856'. Reached TD at 4:00 AM 1-9-2000. Ran 20 joints of 11-3/4" 42# J-55 (856') of casing set at 851'. 1-Texas Pattern notched guide shoe set at 850'. Insert float set at 808'. Cemented with 315 sacks Premium Plus Halliburton Lite, 3% CaCl2, 1/4#/sackflocele and 5#/sack gilsonite (yield 2.02, weight 12.4). Tailed in with 200 sacks Premium Plus and 2% CaCl2 (yield 1.34, weight 14.8). PD 11:00 AM 1-9-2000. Bumped plug to 400 psi, OK. Circulated 97 sacks. WOC. Nippled up and tested to 1000 psi for 15 minutes, OK. Drilled out at 12:15 AM 1-10-2000. WOC 13 hours and 15 minutes. Reduced hole to **Jan 2** 0 2000 14. I hereby certiffy Operations Technician Date Jan. 12, 2000

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements

ROSWELL, NM

JAN 18 2000

BECEINED