Submit 3 Copies to Appropriate
District Office

State of New Mexico Energy, Minerals and Natural Resources Department

Form C-103 Revised 1-1-89

DISTRICT I P.O. Box 1980, Hobbit, NM 88240

חופדפוכד וו

OIL CONSERVATION DIVISION P.O. Box 2088 New Maxico 87504-2088

WELL API NO. 30-005-63229 DATE April 28, 2001

P.O. Drawer DD, Artesia, NM 88210	5. Indicate Type of Lease STATE FEE X
DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410	6. State Oil & Gas Lease No.
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	7. Lease Name or Unit Agreement Name
1. Type of Well: OIL GAS WELL X OTHER	Bestwall ST
2. Name of Operator YATES PETROLEUM CORPORATION	8. Well No.
3. Address of Operator	9. Pool name or Wildcat
105 South 4th St., Artesia, NM 88210	Undesignated Granite
4. Well Location	
Unit Letter M : 660 Feet From The South Line and 66	O Feet From The West Line
Section 20 Township 8S Range 26E	NMPM Chaves County
3697' GR	
11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK	ALTERING CASING
TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLIN	IG OPNS. PLUG AND ABANDONMENT
PULL OR ALTER CASING CASING TEST AND C	EMENT JOB
OTHER: Spud, co	nductor, resume drilling, X casing & cement
12. Describe Proposed of Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.	
Spudded a 26" hole with rat hole machine at 10:00 AM 5-4-20 of 20" conductor pipe. Cemented to surface. NOTE: Notifi operations. Resumed drilling a 12-1/4" hole with rotary to	ed Mike w/OCD-Artesia of
TD 1016'. Reached TD at 8:15 AM 5-17-2000. Ran 24 joints (1000.74') of casing set at 1012'. 1-Texas Pattern notched float set at 970'. Cemented with 450 sacks 65-35-6, 1/4#/s (yield 1.99, weight 12.6). Tailed in with 200 sacks Class weight 14.8). PD 4:15 PM 5-17-2000. Bumped plug to 830#, WOC. Nippled up and tested to 500 psi for 10 minutes, OK. WOC 19 hours and 45 minutes. Reduced hole to 7-7/8". Resu	guide shoe set at 1012'. Insert ack celloflake and 2% CaCl2 C and 2% CaCl2 (yield 1.32, OK. Circulated 118 sacks. Drilled out at 12:00 PM 5-18-2000.
I hereby certify that the information above is true and complete to the best of my knowledge and belief.	

(This space for State Use)

TYPE OR PRINT NAME

Rusty Klein

_ DATE -

TELEPHONE NO. 505/748-1471

APPROVED BY-CONDITIONS OF AFFROVAL, IF ANY: