

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.
30-005-63229

5. Indicate Type of Lease
STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name
Bestwall ST

8. Well No.
2

9. Pool name or Wildcat
Undesignated Granite

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☐ GAS WELL ☒ OTHER

2. Name of Operator
YATES PETROLEUM CORPORATION

3. Address of Operator
105 South 4th St., Artesia, NM 88210

4. Well Location
Unit Letter M : 660 Feet From The South Line and 660 Feet From The West Line
Section 20 Township 8S Range 26E NMPM Chaves County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
3697' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: Production casing & cement <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 6223'. Reached TD at 7:30 AM 6-9-2000. Ran 148 joints of 5-1/2" 15.5# casing as follows: 50 joints of 5-1/2" 15.5# sandblasted (2082.91') and 98 joints of 5-1/2" 15.5# varnished (4139.62') (Total 6222.53') of casing set at 6220'. Float shoe set at 6220'. Float collar set at 6177'. Bottom marker set at 5203'. Top marker set at 4161'. Cemented with 700 sacks Pecos Valley Lite, 4#/sack D-42, 1#/sack D-44, .3% D-13, .2% D-65, .3% D-167 and .2% D-46 (yield 1.34, weight 13.0). PD 8:00 AM 6-13-2000. Bumped plug to 1750 psi for 15 minutes, OK. WOC. Released rig at 2:00 PM 6-13-2000.

Waiting on completion unit.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Operations Technician DATE April 28, 2001

TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY TIM W. GORE
DISTRICT II SUPERVISOR

MAY 15 2001

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: