

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.
30-005-63231

5. Indicate Type of Lease
STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☐ GAS WELL ☒ OTHER

2. Name of Operator
YATES PETROLEUM CORPORATION

3. Address of Operator
105 South 4th St., Artesia, NM 88210

4. Well Location
Unit Letter H : 1980 Feet From The North Line and 1000 Feet From The East Line

Section 3 Township 8S Range 26E NMPM Chaves County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
4581' GR

7. Lease Name or Unit Agreement Name

Coronet TI

Well No.

2

9. Pool name or Wildcat
Pecos Slope Abo

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: Spud, conductor, resume drilling, surface casing & cement ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 26" hole with rat hole machine at 10:20 AM 6-19-2000. Drilled to 40'. Set 40' of 20" conductor pipe. Cemented to surface. NOTE: Notified Mike w/OCD-Artesia of spud. Resumed drilling a 12-1/4" hole with rotary tools at 8:00 PM 7-4-2000.

TD 1024'. Reached TD at 7:00 PM 7-6-2000. Ran 24 joints of 8-5/8" 24# J-55 and 1 landing joint (1027.56') of casing set at 1024'. 1-Texas Pattern notched guide shoe set at 1024'. Insert float set at 982'. Cemented with 650 sacks 65-35 Poz C, 6% D-20, 2% S-1 and 1/4#/sack D-29 (yield 1.99, weight 12.6). Tailed in with 200 sacks "C" with 2% S-1 (yield 1.32, weight 14.8). PD 3:45 AM 7-7-2000. Bumped plug to 450 psi, OK. Circulated 85 sacks. WOC. Nipped up and tested to 500# for 15 minutes, OK. Drilled out at 10:15 PM 7-7-2000. WOC 18 hours and 45 minutes. Reduced hole to 7-7/8". Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Operations Technician DATE Aug. 30, 2000

TYPE OR PRINT NAME Rusty Klein

TELEPHONE NO. 505/748-1471

(This space for State Use)

APPROVED BY Jim W. Green

TITLE District Supervisor

DATE

SEP 12 2000

CONDITIONS OF APPROVAL, IF ANY: