

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89


DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088



WELL API NO.	30-005-63232
5. Indicate Type of Lease	STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.	LG-2622
7. Lease Name or Unit Agreement Name	Harvest ABR State
8. Well No.	2
9. Pool name or Wildcat	Pecos Slope Abo

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR RE-ENTRY"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	NSL Order: R-11325
2. Name of Operator YATES PETROLEUM CORPORATION	
3. Address of Operator 105 South 4th St., Artesia, NM 88210	

4. Well Location Unit Letter C : 660 Feet From The North Line and 2139 Feet From The West Line Section 36 Township 9S Range 24E NMPM Chaves County	10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3561' GR
--	--

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK <input type="checkbox"/> TEMPORARILY ABANDON <input type="checkbox"/> PULL OR ALTER CASING <input type="checkbox"/> OTHER: <input type="checkbox"/>	SUBSEQUENT REPORT OF: REMEDIAL WORK <input type="checkbox"/> COMMENCE DRILLING OPNS. <input type="checkbox"/> CASING TEST AND CEMENT JOB <input type="checkbox"/> OTHER: Spud, conductor, resume drilling, surface casing & cement <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 26" hole with rat hole machine at 12:00 noon 2-10-2000. Drilled to 60'. Set 60' of 20" conductor pipe. Cemented to surface. NOTE: Notified OCD-Artesia of intent to spud. Resumed drilling a 12-1/4" hole with rotary tools at 4:15 AM 2-20-2000.

TD 935'. Reached TD to run casing at 8:15 PM 2-21-2000. Ran 21 joints of 8-5/8" 24# J-55 (881') of casing set at 893'. 1-Texas Pattern notched guide shoe set at 893'. Insert float set at 851'. Cemented with 250 sacks 65-35 Poz C, 6% D-20, 2% S-1 and 1/4#/sack D-29 (yield 1.99, weight 12.6). Tailed in with 200 sacks Class C with 2% S-1 and 1/4#/sack D-29 (yield 1.32, weight 14.8). PD 8:45 AM 2-22-2000. Bumped plug to 421 psi, OK. Cement did not circulate. WOC 3 hours. Ran 1" and tagged cement at 75'. Spotted 104 sacks Class C with 4% CaCl2. PD 12:15 PM 2-22-2000. Circulated 14 sacks to pit. WOC. Nippled up and tested to 500# for 15 minutes, OK. Drilled out at 2:45 AM 2-23-2000. WOC 18 hours. Reduced hole to 7-7/8". Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Operations Technician DATE May 16, 2000

TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY BGA TIM W. GUM
DISTRICT II SUPERVISOR

APPROVED BY _____ TITLE _____ DATE MAY 23 2000

CONDITIONS OF APPROVAL, IF ANY: