

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

OIL CONSERVATION DIVISION  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

WELL API NO.  
30-005-63233

5. Indicate Type of Lease  
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.  
LG-2462

7. Lease Name or Unit Agreement Name  
Conejo RH State

8. Well No.  
5

9. Pool name or Wildcat  
Wildcat Precambrian

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO  
DIFFERENT RESERVOIR. USE APPLICATION FORM FOR DEEPENING OR PLUG BACK  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:  
OIL WELL ☐ GAS WELL ☒ OTHER ☐

2. Name of Operator  
YATES PETROLEUM CORPORATION

3. Address of Operator  
105 South 4th St., Artesia, NM 88210

4. Well Location  
Unit Letter F : 1500 Feet From The North Line and 1980 Feet From The West Line  
Section 2 Township 7S Range 25E NMPM Chaves County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)  
3758' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐  
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐  
CASING TEST AND CEMENT JOB ☐  
OTHER: Resume drilling, surface casing & cmt ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Resumed drilling a 14-3/4" hole with rotary tools at 10:30 PM 4-25-2000.

TD 900'. Reached TD to run casing at 11:00 PM 4-27-2000. Ran 21 joints of 11-3/4" 42# H-40 (902.52') of casing set at 900'. 1-Texas Pattern notched guide shoe set at 900'. Insert float set at 859'. Cemented with 360 sacks 65-35 Poz C, 6% D-20, 2% S-1 and 1/4#/sack D-29 (yield 2.14, weight 12.6). Tailed in with 300 sacks Class C with 2% S-1 (yield 1.32, weight 14.8). PD 7:10 AM 4-28-2000. Bumped plug to 750 psi, OK. Circulated 93 sacks. WOC. Nippled up and tested to 500 psi for 30 minutes. Drilled out at 1:15 AM 4-29-2000. WOC 18 hours and 5 minutes. Reduced hole to 11". Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Operations Technician DATE June 29, 2000

TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY THE DISTRICT II SUPERVISOR  
DISTRICT II SUPERVISOR 664

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE JUL 03 2000

CONDITIONS OF APPROVAL, IF ANY: