L			- 108		
Submit 3 Copies	State of New Mexico Energy, anerals and Natural Resources Department		11	Form C-103	
to Appropriate District Office	energy,nerais and Natural R	esources Department	<i>P</i> () •	Revised 1-1-89	
DISTRICT I P.O. Box 1980, Hobbs, NM 88240	OIL CONSERVATION P.O. Box 20		WELL API NO.		
DISTRICT II P.O. Drawer DD, Artesia, NM 88210	Santa Fe, New Mexico	87504-2088	30-005-632 5. Indicate Type of Lease		
DISTRICT III	262128293037		STATE XX FEE		
1000 Rio Brazos Rd., Aztec, NM 87410	753 20 E	1520 A 25		6. State Oil & Gas Lease No. LG-2462	
(DO NOT USE THIS FORM FOR PRO	CES AND REPORTS ON WE PROSALS TO DRILL OF TO DEEPEN RIVOIR. USE APPLICATION FOR ALLOID FOR SUCH PROPOSALS OF THE PROP	POR POOR BACKUTO A	7. Lease Name or Unit Agreeme	mt Name	
OEL GAS X	OTHER CO.	3/	Conejo RH St	ate	
2. Name of Operator	8141	Digiple 121	8. Well No.		
YATES PETROLEUM CORPORATION 3. Address of Operator			5		
105 South 4th St., Art	esia. NM 88210		9. Pool name or Wildcat Wildcat Precambi	rian	
4. Well Location					
Unit Letter F: 150	O Feet From The North	Line and1980	Feet From The We	St Line	
Section 2			NMPM Chaves	County	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3758 GR					
11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data					
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:					
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	ALTERING (CASING	
TEMPORARILY ABANDON	CHANGE PLANS	COMMENCE DRILLING	OPNS. DLUG AND	ABANDONMENT 🗌	
PULL OR ALTER CASING		CASING TEST AND CEMENT JOB			
OTHER:		OTHER: Product	ion casing & cement	X	
12. Describe Proposed or Completed Operations (Clearly state all perinent details, and give perinent dates, including estimated date of starting any proposed work) SEE RULE 1103. TD 5180'. Reached TD at 12:00 midnight 5-11-2000. Ran 122 joints of 5-1/2" 15.5# casing as follows: 39 joints of 5-1/2" 15.5# sandblasted (1644.23') and 83 joints of 5-1/2" 15.5# varnished (3536.22') (Total 5180.45') of casing set at 5179'. Float shoe set at 5179'. Float collar set at 5136'. Cemented with 558 sacks Ultra Lite C, 5#/sack D-42, 1/4#/sack D-44, .35% D-65, .35% D-156 and .2% D-45 (yield 1.69, weight 13.0). PD 7:20 PM 5-14-2000. Bumped plug to 1200 psi for 15 minutes, OK. WOC. Released rig at 11:00 PM 5-14-2000.					

mme Operations Technician

(This space for State Use)

TYPE OR PRINT NAME

ORIGINAL SIGNED BY TIM W. GUM DISTRICT II SUPERVISOR 1564

DATE JUL 0 3 2000

DATE June 29, 2000

TELEPHONE NO. 505/748-1471

Rusty Klein

CONDITIONS OF APPROVAL, IF ANY: