	ask
Submit 3 Copies To Appropriate District Office State of New Mexico	Form C-103
District I Energy, Minerals and Natural Resources	WELL API NO.
1625 N. French Dr., Hobbs, NM 88240 District II W.H. South First, Artesia, NM 88210 OIL CONSERVATION DIVISION	30-005-63234
811 South First, Artesia, NM 88210 District III 1220 South St. Francis Dr.	5. Indicate Type of Lease
1000 Rio Brazos Rd., Aztec, NM 87410 District IV Santa Fe, NM 87505	STATE X FEE 6. State Oil & Gas Lease No.
1220 S. St. Francis Dr., Santa Fe, NM 87505	LG-939
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A	7. Lease Name or Unit Agreement Name:
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	Witz VN State
1. Type of Well: Oil Well Gas Well X Other	
2. Name of Operator	7. Well No.
Yates Petroleum Corporation 3. Address of Operator	#4 8. Pool name or Wildcat
105 S. 4th Street Artesia, NM 88210	Wildcat Precambrian
10 10 10 10 10 10 10 10 10 10 10 10 10 1	
4. Well Location	
Unit Letter F: 1980 feet from the North line and 1980 feet from the West line	
Section 26 Township 9S Range 26E NMPM Chaves County	
10. Elevation (Show whether DR, RKB, RT, GR, etc.	
3801' GR	
11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:	
	ALTERING
	CASING
TEMPORARILY ABANDON CHANGE PLANS COMMENCE DR	ABANDONMENT
PULL OR ALTER CASING MULTIPLE CASING TEST A CEMENT JOB	ND
OTHER: OTHER: set and	cement production casing X
Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of	
starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.	
9/4/00 Reached TD at 6676' at 4:30 PM.	
9/5/00 - Run logs and sidewall cores.	
9/6/00 Ran 161 joints (6686.93') casing set at 6676' as follows: 56 joints 5-1/2" 15.5# J-55 SB (2319.72')	
105 joints 5-1/2" 15.5# J-55 MV (4367.21')	
Float shoe set at 6676'. Float collar set at 6633.81'. Bottom marker set at 4356.28'. Cemented with 625 sxs Pecos Valley Lite with 1 pps D44 + 4 pps D42 + .2% D65 + .3% D167 + .2% D46 + .15% D13	
(yld1.42, wt 13).	
9/7/00 Plug down at 12:30 AM. Bumped plug to 1840 psi for 2 mins, held OK.	
Released rig at 6:30 AM 9/7/00.	
I hereby certify that the information above is true and complete to the best of my knowledge and belief.	
SIGNATURE Might TITLE Engineering Technician DATE January 10, 2002	
Type or print name Susan Herpin Telephone No. 505-748-1471	
(This space for State use) ORIGINAL SIGNED BY TIM W. GUM	
APPPROVED BY DISTRICT II SUPERVISOR TITLE DATUM 1 4 2002 Conditions of approval, if any	