

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 South First, Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103
Revised March 25, 1999

WELL API NO.

30-005-63238

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name:

Fred ASY Com

7. Well No.

#1

8. Pool name or Wildcat

Pecos Slope Abo

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☒ Other ☐

2. Name of Operator

Yates Petroleum Corporation

3. Address of Operator

105 S. 4th Street Artesia, NM 88210

4. Well Location

Unit Letter **B** : **700** feet from the **North** line and **1980** feet from the **East** line

Section **12**

Township **5S**

Range **24E**

NMPM

Chaves

County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

3865' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

REMEDIAL WORK ☐

ALTERING CASING ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

COMMENCE DRILLING OPNS. ☒

PLUG AND ABANDONMENT ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETION ☐

CASING TEST AND CEMENT JOB ☐

OTHER:

OTHER:

Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

1/22/01 - Spud 20" hole with rathole machine at 10:00 AM. Set 40' of 16" conductor pipe, cemented to surface.

1/23/01 - Resumed drilling with rotary tool, 12-1/4" hole, at 10:45 PM.

1/25/01 - Reached TD of surface hole at 904' at 12:15 PM. Ran 21 joints (903.67') 8-5/8" 24# casing set at 904'. Texas pattern guide shoe set at 903.67'. Insert float set at 861.08'. Cemented with 400 sxs 35:65:6 C + 2% CaCl2 + 1/8 pps floreal (yld 1.99, wt 12.6). Tailed in with 200 sxs C + 2% CaCl2 (yld 1.32, wt 14.8). PD at 7:00 PM. Bumped plug to 925#, held OK. Circ 56 sxs. WOC.

1/26/01 - Drilled out at 4:30 PM. WOC 21-1/2 hours.

Reduced hole to 7-7/8" and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE

Engineering Technician

DATE

January 21, 2002

Type or print name

Susan Herpin

Telephone No. 505-748-1471

(This space for State use)

ORIGINAL SIGNED BY TIM W. GUN
DISTRICT II SUPERVISOR

APPROVED BY

TITLE

DATE

JAN 30 2002

Conditions of approval, if any: