

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 South First, Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

C15F
up

Form C-103

Revised March 25, 1999

WELL API NO.

30-005-63241

5. Indicate Type of Lease

STATE ☒

FEE ☐

6. State Oil & Gas Lease No.

LG-2621

7. Lease Name or Unit Agreement Name:

Thunderhead TD State Com

7. Well No.

#4

8. Pool name or Wildcat

Wildcat Pre-Cambrian

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS.)

1. Type of Well:

Oil Well ☐

Gas Well ☒

Other ☐

2. Name of Operator

Yates Petroleum Corporation

3. Address of Operator

105 S. 4th Street Artesia, NM 88210

4. Well Location

Unit Letter E : 1980 feet from the North line and 660 feet from the West line

Section 32 Township 8S Range 26E NMPM Chaves County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

3741' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

MULTIPLE
COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND
ABANDONMENT ☐

CASING TEST AND
CEMENT JOB ☐

OTHER: set production casing, cement ☐

Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

7/3/00 - Ran 161 jts (6764.92') 5-1/2" 15.5# J-55 casing set at 6740'. Float shoe set at 6740'. Float collar set at 6697.05. Bottom marker set at 4209.55'. Cemented with 1152 sxs Pecos Valley Lite with 1 pps D45 + 2% D65 + .3% D167 + .2% D46 + .3% D13 (yld 1.34, wt 13). PD 7:40 AM. Bumped plug to 1800 psi for 1 min. Held OK. Rig released at 11:45 AM.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Susan Herpin TITLE Engineering Technician DATE September 24, 2001

Type or print name Susan Herpin

Telephone No. 505-748-1471

(This space for State use)

ORIGINAL SIGNED BY TIM W. GUM

APPROVED BY DISTRICT II SUPERVISOR TITLE

DATE OCT 03 2001

Conditions of approval, if any: