			-		0/51-
Form 3160-5 (August 1999)_	UNITED STATES DEPARTMENT OF THE IN BUREAU OF LAND MANAG	TERIOR	N.M. Oil Cons	FORM APPROVED OMB No. 1004-0135 Division Division Division	
CUNDE			811 S. 1st Stre	NM-29211	
Do not use ti abandoned w	his form for proposals to o ell. Use Form 3160-3 (APD)	drill or to re-en for such prop	artesia, NM 88 osals.	NM-29211 261 0F 2834 lottee or Tribe Nam	e
SUBMIT IN TR	NPLICATE - Other instru	ctions on reve	erse side	7. If Unit or CA/Agreement, Name	and/or No.
1. Type of Well					
🔲 Oil Well 🖾 Gas Well 🛄 Other				8. Well Name and No.	
2. Name of Operator Yates Petroleum Corporation				9. API Well No.	
3a. Address		3b. Phone No. (include area code)		30-005-63244	
105 S. 4th St Artesia, NM 88210		505-748-1471n Refer		10. Field and Pool, or Exploratory Area	
4. Location of Well (Footage, Sec				Undesignated	
990' FNL & 840' F	YEL of Section 4-T9S	-R26E (Unit	A, NENE)	11. County or Parish, State	
				Chaves Co., NM	
12. CHECK AI	PPROPRIATE BOX(ES) TO	INDICATE NA	TURE OF NOTICE, R	EPORT, OR OTHER DATA	
TYPE OF SUBMISSION	TYPE OF ACTION				
	[				<u> </u>
Notice of Intent	Acidize	Deepen Fracture Treat	Production (Star	· · · · · · · ·	
	Casing Repair	New Constructi		Other Spud,	conductor,
Subsequent Report		Plug and Aband	ion 🔲 Temporarily At		lg, surface
Final Abandonment Notice	Convert to Injection	Plug Back	<b>Water</b> Disposal	casing & d	cement
Attach the Bond under which the following completion of the invi- testing has been completed. Find determined that the site is ready Spudded a 26" hole of 20" conductor p spud. Resumed dri	he work will be performed or prov volved operations. If the operation inal Abandonment Notices shall be for final inspection.) with rat hole mach	ide the Bond No. or results in a multiple filed only after all ine at 2:45 urface. NC e with rota	n file with BLM/BIA. Requi completion or recompletion requirements, including recl PM 6-19-2000. DTE: Notified St	ue vertical depths of all pertinent mark ired subsequent reports shall be filed v in a new interval, a Form 3160-4 shall amation, have been completed, and the Drilled to 40'. Set tan Mayo w/BLM-Roswell O AM 6-26-2000. Noti:	within 30 days I be filed once e operator has 40' 1 of
no returns. Drill conductor and ceme 2nd load - dumped 3rd load - dumped TD 1120'. Reached casing set at 1120	ed from 85-173' wit ented with 8 yards o 8 yards of ready-mi 3 yards of ready-mi 1 TD at 12:00 PM 6-2 )'. 1-Texas Pattern	h no return f ready-mix x down cond x down cond 7-2000. Ra notched gu	ns. Laid down d x. Top of cemen ductor. Top of ductor. Topped an 27 joints of a nide shoe set at	-85' while pumping pi rill string. Cut win t at approximately 61 cement at approximate out - did not fall ba 8-5/8" 24# J-55 (1138 1120'. Insert float 4#/sack D-29 (yield 1	dow in '. ly 50'. ck. .59') of set at
14. I hereby certify that the foregoi Name (Printed/Typed)	ng is true and correct		CONTINUE	D ON NEXT PAGE:	
Rusty Klein		Titl	Title Operations Technician		
Rusty Reem	KI.		operaciono re	Charle Fun	
Signature Pusty	Then	Dat	<sup>e</sup> Sept. 15, 200	0	
1 0	THIS SPACE FO	OR FEDERAL O	R STATE OFFICE USE		
Approved by Conditions of approval, if any, are certify that the applicant holds leg which would entitle the applicant to	al or equitable title to those rights conduct operations thereon.	in the subject leas	e Office	Date 7 CORD	
Title 18 U.S.C. Section 1001 and T States any false, fictitious or fraudu	itle 43 U.S.C. Section 1212, make i lent statements or representations as	t a crime for any pe to any matter within	rson knowingly and willfully n its jurisdiction.	to make to any department of agency	of the United
			,	and the second se	

YATES PETROLEUM CORPORATION Engwall RL Federal #3 Section 4-T9S-R26E Chaves County, New Mexico

## SUNDRY NOTICE CONTINUED:

weight 14.2) and 552 sacks 65-35 Poz C, 6% D-20, 2% S-1 and 1/4#/sack D-29 (yield 1.99, weight 12.6). Tailed in with 201 sacks "C" and 2% S-1 (yield 1.32, weight 14.8). PD 6:48 PM 6-27-2000. Bumped plug to 600 psi, OK. Cement did not circulate. WOC 5 hours. Ran 1". Tagged cement at 152'. Spotted 90 sacks "C" with 3% CaCl2. PD 1:30 AM 6-28-2000. WOC 2-1/2 hours. Ran 1". Tagged cement at 112'. Spotted 90 sacks "C" with 3% CaCl2. PD 3:32 AM 6-28-2000. WOC 2-1/4 hours. Ran 1". Tagged cement at 85'. Spotted 90 sacks "C" with 3% CaCl2. PD 6:10 AM 6-28-2000. WOC 2 hours. Ran 1". Tagged cement at 78'. Spotted 90 sacks "C" and 3% CaCl2. PD 8:10 AM 6-28-2000. Circulated 21 sacks to pits. WOC. Nippled up and tested to 500 psi for 15 minutes, OK. Drilled out at 2:00 AM 6-29-2000. WOC 31 hours and 30 minutes. Reduced hole to 7-7/8". Resumed drilling. NOTE: Stan Mayo w/BLM-Roswell witnessed.

Rusty Klein

Operations Technician Sept. 15, 2000