

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO.  
30-005-63253

5. Indicate Type of Lease  
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.  
V-4507

7. Lease Name or Unit Agreement Name

Samedan ATH State

8. Well No.

2

9. Pool name or Wildcat  
Wildcat Ordovician

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL  
WELL ☐

GAS  
WELL ☒

OTHER ☐

2. Name of Operator

YATES PETROLEUM CORPORATION

3. Address of Operator

105 South 4th St., Artesia, NM 88210

4. Well Location

Unit Letter P : 660 Feet From The South Line and 660 Feet From The East Line

Section 35

Township 10S

Range 26E

NMPM

Chaves

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3695' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: Production casing & cement ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 6205'. Reached TD at 5:00 AM 6-21-2000. Ran 148 joints of 5-1/2" 15.5# J-55 casing as follows: 42 joints of 5-1/2" 15.5# sandblasted (1761.61') and 106 joints of 5-1/2" 15.5# J-55 varnished (4459.95') (Total 6221.58') of casing set at 6205'. Float collar set at 6179'. Bottom marker set at 4443'. Pumped 100 bbls of mud with 150 scf/N2 per bbl ahead of 700 sacks "C", 3% D-79, 1% S-1, 1/4#/sack D-29 (yield 2.80, weight 11.5). Tailed in with 450 sacks Pecos Valley Lite, 1#/sack salt, 4#/sack D-42, .2% D-65, .3% D-167, .2% D-40 and .3% D-13 (yield 1.34, weight 13.0). PD 7:05 AM 6-23-2000. Bumped plug to 1666 psi for 5 minutes, OK. Circulated 108 sacks. WOC. Released rig at 11:00 AM 6-23-2000.

Waiting on completion unit.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

*Rusty Klein*

TITLE

Operations Technician

DATE

TYPE OR PRINT NAME

Rusty Klein

TELEPHONE NO. 505/748-1471

(This space for State Use)

SUPERVISOR, DISTRICT II

APPROVED BY

TITLE

DATE

8-25-00

CONDITIONS OF APPROVAL, IF ANY: