State of New Mexico Form C-103 Submit 3 Copies Energy, Minerals and Natural Resources Department Revised 1-1-89 to Appropriate District Office OIL CONSERVATION DIVISION DISTRICT WELL API NO. P.O. Box 1980, Hobbs, NM 88240 P.O. Box 2088 30-005-63259 Santa Fe. New Mexico 87504-2088 DISTRICT II P.O. Drawer DD, Artesia, NM 88210 5. Indicate Type of Lease STATE FEE 📋 DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410 6. State Oil & Gas Lease No. V = 5524SUNDRY NOTICES AND REPORTS ON WELLS DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMET LES (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK 7. Lease Name or Unit Agreement Name 1. Type of Well: WELL X WELL OTHER Avenue AVU State 2. Name of Operator 8. Well No. YATES PETROLEUM CORPORATION 3. Address of Operator 9. Pool name or Wildcat 105 South 4th St., Artesia, NM 88210 Undesignated 4. Well Location 1500 Feet From The _ South 660 Line and Feet From The Line 26E Chaves 21 hip 9S Range 26E 10. Elevation (Show whether DF, RKB, RT, GR, etc.) **NMPM** Township County 3767' GR Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: **ALTERING CASING** PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK **TEMPORARILY ABANDON CHANGE PLANS** COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT **PULL OR ALTER CASING** CASING TEST AND CEMENT JOB OTHER: Spud, conductor, resume drilling, OTHER: surface casing & cement 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. Spudded a 20" hole with rat hole machine at 12:30 PM 8-19-2000. Drilled to 40'. Set 40' of 16" conductor pipe. Cemented to surface. NOTE: Notified OCD-Artesia answering service of spud. Resumed drilling a 12-1/4" hole with rotary tools at 6:30 PM 8-21-2000. TD 1106'. Reached TD at 8:15 AM 8-24-2000. Ran 26 joints of 8-5/8" 24# J-55 (1107.18') of casing set at 1106'. 1-Texas Pattern notched guide shoe set at 1105'. Insert float set at 1063'. Cemented with 500 sacks Class C Poz (65-35-6), 6% D-20, 2% S-1, 1/4#/sack D-29 (yield 1.99, weight 12.6). Tailed in with 200 sacks Class C with 2% CaCl2 (yield 1.32, weight 14.8). PD 4:20 PM 8-24-2000. Bumped plug to 680 psi, OK. Circulated 36 sacks. WOC. Nippled up and tested to 500 psi for 15 minutes, OK. Drilled out at 12:00 Noon 8-25-2000. WOC 19 hours and 50 minutes. Reduced hole to 7-7/8". Resumed drilling. complete to the best of my knowledge and belief. I hereby certify that Operations Technician Nov. 30, 2000 SKINATURE

TITLE

TELEPHONE NO. 505/748-1471

NOV 3 0 2000

DATE

CONDITIONS OF AFFROVAL, IF ANY:

TYPE OR PRINT NAME

APPROVED BY

(This space for State Use)

Rusty Klein

SUPERVISOR, DISTRICT II