

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87411

OIL CONSERVATION DIVISION
P.O. Box 2083
Santa Fe, New Mexico 87504-2083

WELL API NO.
30-005-63261

5. Indicate Type of Lease
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.
VO-5523

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☐ GAS WELL ☒ OTHER

2. Name of Operator
YATES PETROLEUM CORPORATION

3. Address of Operator
105 South 4th St., Artesia, NM 88210

4. Well Location
Unit Letter A : 990 Feet From The North Line and 660 Feet From The East Line

Section 21 Township 9S Range 26E NMPM Chaves County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
3767' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: Spud, conductor, resume drilling, surface casing & cement ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 20" hole with rat hole machine at 10:30 AM 9-15-2000. Drilled to 40'. Set 40' of 16" conductor pipe. Cemented to surface. NOTE: Notified Betty w/OCD-Artesia. Resumed drilling a 12-1/4" hole with rotary tools at 3:15 AM 10-6-2000.

TD 1134'. Reached TD at 1:00 PM 10-7-2000. Ran 27 joints of 8-5/8" 24# J-55 8rd (1133.98') of casing set at 1134'. 1-Texas Pattern notched guide shoe set at 1133'. Insert float set at 1094'. Cemented with 350 sacks Poz 65-35, 6% D-20, 2% CaCl2 and 1/4#/sack D-29 (yield 1.99, weight 12.6). Tailed in with 200 sacks "C" with 2% CaCl2 (yield 1.32, weight 14.8). PD 8:00 PM 10-7-2000. Bumped plug to 350 psi, held okay. Circulated 27 sacks. WOC. Nipped up and tested to 500 psi for 15 minutes. Drilled out at 2:00 PM 10-8-2000. WOC 18 hours. Reduced hole to 7-7/8". Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Rusty Klein

TITLE Operations Technician

DATE Nov. 30, 2000

TYPE OR PRINT NAME

Rusty Klein

TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY TIM W. GUN
DISTRICT II SUPERVISOR

JUL 26 2001

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: