

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-005-63269
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name  Percentage APR
8. Well No. 1
9. Pool name or Wildcat Pecos Slope Abo

SUNDRY NOTICES AND REPORTS ON WELLS A  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER	2. Name of Operator YATES PETROLEUM CORPORATION
3. Address of Operator 105 South 4th St., Artesia, NM 88210	10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3793' GR
4. Well Location Unit Letter 0 : 660 Feet From The South Line and 1650 Feet From The East Line Section 3 Township 8S Range 26E NMPM Chaves County	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐  
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐  
CASING TEST AND CEMENT JOB ☐  
OTHER: Spud, conductor, resume drilling, surface casing & cement ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 20" hole with rat hole machine at 11:10 AM 9-1-2000. Drilled to 40'. Set 40' of 16" conductor pipe. Cemented to surface. Resumed drilling a 12-1/4" hole with rotary tools at 6:00 AM (CST) 9-8-2000.

TD 1018'. Reached TD at 7:45 AM (CST) 9-9-2000. Ran 24 joints of 8-5/8" 24# J-55 (1018.79') of casing set at 1018'. 1-Texas Pattern notched guide shoe set at 1016'. Insert float set at 974'. Cemented with 600 sacks 65-35 Pooz C, 6% D-20, 2% CaCl2 and 1/4#/sack D-29 (yield 1.99, weight 12.6). Tailed in with 200 sacks "C" with 2% CaCl2 and 1/4#/sack D-29 (yield 1.32, weight 14.8). PD 3:15 PM 9-9-2000. Bumped plug to 450 psi. Cement did not circulate. WOC 4-1/2 hours. Ran Temperature Survey and found top of cement at 300'. Ran 1". Tagged cement at 298'. Spotted 25 sacks "C" with 4% CaCl2. PD 9:45 PM 9-9-2000. WOC 1 hour. Ran 1". Tagged cement at 298'. Spotted 50 sacks "C" and 4% CaCl2. PD 11:20 PM 9-9-2000. WOC 1 hour. Ran 1". Tagged cement at 258'. Spotted 50 sacks "C" with 4% CaCl2. PD 1:00 AM 9-10-2000. WOC 1 hour. Ran 1". Tagged cement at 228'.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

CONTINUED ON NEXT PAGE:

SIGNATURE Rusty Klein TITLE Operations Technician DATE Nov. 30, 2000  
TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY TIM W. GUM  
DISTRICT II SUPERVISOR


JAN 16 2001

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

YATES PETROLEUM CORPORATION  
Percentage APR #1  
Section 3-T8S-R26E  
Chaves County, New Mexico

SUNDRY NOTICE CONTINUED:

Spotted 100 sacks "C" with 4% CaCl<sub>2</sub>. PD 3:00 AM 9-10-2000. Had mud to surface on 4th stage of cement. Continued pumping until cement came to surface. Circulated 11 sacks of good cement to pits. WOC. Nippled up and tested to 500# for 15 minutes, OK. Drilled out at 5:45 PM 9-10-2000. WOC 26 hours and 30 minutes. Reduced hole to 7-7/8". Resumed drilling.

  
\_\_\_\_\_  
Rusty Klein  
Operations Technician  
November 30, 2000