

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO.  
30-005-63281

5. Indicate Type of Lease  
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.  
LG-4916

7. Lease Name or Unit Agreement Name  
Sandlewood AEW State

8. Well No.  
2

9. Pool name or Wildcat  
Foor Ranch Pre-Permian

10. Elevation (Show whether DF, RKB, RT, GR, etc.)  
3975' GR

SUNDRY NOTICES AND REPORTS ON WELL 30-005-63281-122  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT  
(FORM C-101) FOR SUCH PROPOSAL

1. Type of Well:  
OIL WELL ☐ GAS WELL ☒ OTHER ☐

2. Name of Operator  
YATES PETROLEUM CORPORATION

3. Address of Operator  
105 South 4th St., Artesia, NM 88210

4. Well Location  
Unit Letter E : 1500 Feet From The North Line and 660 Feet From The West Line

Section 31 Township 8S Range 27E NMPM Chaves County

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: Spud, conductor, resume drilling, surface casing & cement <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 20" hole with rat hole machine at 4:30 PM 10-5-2000. Drilled to 40'. Set 40' of 16" conductor pipe. Cemented to surface. NOTE: Notified OCD-Artesia answering service of operations. Resumed drilling a 12-1/4" hole with rotary tools at 4:30 AM 10-17-2000.

TD 1007'. Reached TD at 11:00 PM 10-17-2000. Ran 24 joints of 8-5/8" 24# J-55 (1010') of casing set at 1007'. 1-Texas Pattern notched guide shoe set at 1007'. Float collar set at 965'. Cemented with 400 sacks Poz C (65-35) and 200 sacks Class C with 2% CaCl2 (yield 1.32, weight 14.8). PD 5:15 PM 10-18-2000. Bumped plug to 1200 psi, OK. Circulated 36 sacks. WOC. Nipped up and tested to 500 psi for 30 minutes, OK. Drilled out at 11:45 AM 10-19-2000. WOC 18 hours and 30 minutes. Reduced hole to 7-7/8". Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Operations Technician DATE April 28, 2001

TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-1471

(This space for State Use)

APPROVED BY SUPERVISOR, DISTRICT II TITLE \_\_\_\_\_ DATE APR 28 2001

CONDITIONS OF APPROVAL, IF ANY: