CONDITIONS OF APPROVAL, IF ANY:

State of New Mexico

C15 Pp	
--------	--

د/۶	qo
API NO.	

Submit 3 Copies to Appropriate District Office	State of New Mexico Energy, Minerals and Natural Resources Department			C12/0	Form C-103 Revised 1-1-89
DISTRICT I P.O. Box 1980, Hobbs, NM 88240	OIL CONSERVATION DIVISION P.O. Box 2088			WELL API NO. 30-005-63	281
DISTRICT II P.O. Drawer DD, Artesia, NM 88210	Santa Fe. New Mexico 87504-2088		5 Indicate Type of Lease	ATEKX FEE	
DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87419				6. State Oil & Gas Lease No LG-4916	0.
(DO NOT USE THIS FORM FOR P DIFFERENT REG (FORM	TICES AND REPORTS OF ROPOSALS TO DRILL OR TO DE ERVOIR. USE "APPLICATION F C-101) FOR SUCH PROPOSAL	EEPEN FOR PER	OR PL UG BAG K TO A	7. Lease Name or Unit Agr	sement Name
1. Type of Well: OIL GAS WELL WELL WELL	OTHER	262	100 mg/s	Sandlewood AE	W State
2. Name of Operator YATES PETROLEUM CORPO	RATION	2425	RECEIVED OCD ARTESIA	8. Well No.	
3. Address of Operator	ctesia, NM 88210	100	000 : 100	9. Pool name or Wildcat	na Darmian
105 South 4th St., At	tesia, Nr. 00210	/c		Foor Ranch Pr	e-rermian
	00 Feet From The North	n	660 660 660 660 660 660 660 660 660 660	Feet From The	West Line
	////////	whether 1 3975	DF, RKB, RT, GR, etc.) GR Nature of Notice, R	SEQUENT REPOR	RT OF:
PERFORM REMEDIAL WORK	PLUG AND ABANDON		REMEDIAL WORK		NG CASING
TEMPORARILY ABANDON []	CHANGE PLANS		COMMENCE DRILLING	[]	AND ABANDOHMEN (
PULL OR ALTER CASING			CASING TEST AND CE		ent X
other:		_	OTHER: Product	ion casing & cem	ent X
12. Describe Proposed or Completed Cowork) SEE RULE 1103. TD 6917'. Reached Tollows: 9 joints of 15.5# J-55 sandblast (3918.27') (Total 69 set at 5872'. Bottom sacks Pecos Valley In D-13 (yield 1.42, we ment. Plug at approximately 1000 of 1000 o	TD at 5:30 AM 11-9-2 of 5-1/2" 17# J-55 sted (2645.57') with 12.56') of casing stem marker set at 656 dite, 1#/sack D-44, eight 13.0). Did no eximately 6033'. WO	2000. sandbl marke set at 8'. 4#/sa ot bum	Ran 164 joints asted (348.72') er and 92 joints 6912'. Float Top marker set ack D-42, .2% D- p plug - bridge Released rig at	s of 5-1/2" 17# & with marker; 63 s of 5-1/2" 15.5# shoe set at 6912 at 3923'. Cemen 65, .3% D-167, .ed off 20 bbls sh	15.5# casing as joints of 5-1/2" J-55 varnished '. Float collar ted with 500 2% D-46 and .15% ort on displace-
Waiting on completion	on unit.				
\mathcal{A}	,				
I hereby certify that the information above	true and complete to the best of my know	wiedge and	odia. Operations I	'ochnician	Amm41 20 2001
SIGNATURE 9 WOLLS	un	т	TE OPERATIONS I	DAT	April 28, 2001

TYTEOR PRINT NAME Rusty Klein	<u>тецерноме но. 505/748-1471</u>
(This space for State Use) \$UPERFINOR, DISTRICT II	APR 28 2001
APPROVED BY TITLE	DATE