

Yates Petroleum Corporation
Sandlewood AEW State #2
Section 31-T-8S-R27E
Chaves County, New Mexico

#26: Perforations

4760' - 4 squeeze holes
4710' - 4 squeeze holes
6664-6670' w/24 .42" holes
6532-6614' w/64 .42" holes
6458-6498' w/42 .42" holes
6300-6394' w/90 .42" holes
6230-6288' w/234 .42" holes
4745-5141' w/38 .42" holes

#27: ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

<u>DEPTH INTERVAL</u>	<u>TREATMENT</u>
6664-6670'	Acidized with 1000 gallons 20% iron control HCL acid
6610-6614'	Acidized with 700 gallons 20% iron control HCL acid & ball sealers
6532-6544'	Acidized with 1000gallons 20% iron control HCL acid & ball sealers
6458'-6498'	Acidized with 1000 gallons 20% iron control HCL acid & ball sealers
6364-6394	Acidized with 1200 gallons of 15% iron control HCL acid
6300-6394'	Acidized with 2800 gallons 15% iron control HCL acid ball sealers
6230-6288'	Acidized with 4000 gallons 7 ½% iron control HCL acid & ball sealers