Submit 3 Copies To Appropriate District Office District I 1625 N. French Dr., Hobbs, NM 88240 District III 811 South First. Artesia, NM 88210 District III 1000 Rio Brazos Rd., Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505 SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)			Form C-103 Revised March 25. 1999 WELL API NO. 30-005-63306 5. Indicate Type of Lease STATE X FEE 6. State Oil & Gas Lease No. VA-2066 7. Lease Name or Unit Agreement Name: Wager "AWG" State		
1. Type of Well: Oil Well Gas Well X	Ot 1er		Á		
2. Name of Operator				7. Well No.	
Yates Petroleum Corporation —				#4	
3. Address of Operator 105 S. 4th Street Artesia, Nivi 88210 8. Pool name or Wildcat Wildcat Ordovician					
4. Well Location					
Unit Letter D : 660 Feet from the North line and 660 feet from the line					
Section 34		Range		NMPM Chave:	County
10. Elevation (Show whether DR, RKB, RT, GR, etc.)					
3786' GR 11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data					
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:					
PERFORM REMEDIAL WORK	PLUG AND ABANDON		REMEDIAL WOR		ALTERING CASING
TEMPORARILY ABANDON	CHANGE PLANS		COMMENCE DRILLING OPNS. X PLUG AND ABANDONMENT		
PULL OR ALTER CASING	MULTIPLE COMPLETION		CASING TEST AI CEMENT JOB	ND	
OTHER:			OTHER:		
Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation. 11/15/00 – Drilled 40' of 26" conductor hole. Set 40' of 20" conductor pipe, cement to surface. 11/16/00 – Resume drilling with rotary tool at 5:00 AM. 11/17/00 – TD 12-1/4" hole. Ran 26 jts. (1100') 8-5/8" 24# J-55 csg. set at 1100'. Texas Pattern Notched Guide Shoe set at 1099'. Float collar set at 1058.87'. Cemented with 400 sxs 35/65 POZ "C" + 1/4# Celloflake 2% CaCl2 (yld 1.99, wt 12.6) Tailed in with 20') sxs "C" 2% CaCl2 (yld 1.32, wt 14.8) PD 10:45 AM. Bumped plug to 1100 psi. Held OK. Circ 20 sxs. WOC. 11/18/00 – Drill out at 8:45 AM. WC)C 22 hrs. Reduced hole to 7-7/8" and resumed drilling. 12/5/00 – Reached TD of 6340' at 5:15 AM. 12/6/00 – Logging. Loggers TD 635.5'.					
I hereby certify that the information above is true and complete to the best of my knowledge and belief.					
SIGNATURE James 1	\$			Technician DA	ATE August , 2001
Type or print name Susan He	rnin			Telenhone	No. 505-748-1471
(This space for State use) ORIG	NAL SIGNED BY TIM	W. GUN	1	Totopholic	AU6 2 9 2001