

Yates Petroleum Corporation
Wager AWG State #4
API 30-005-63306
Section 34 T9S R26E
Chaves County, NM

26. Perforation record (interval, size, and number)

Ordovician	5980-5990'	40 holes	.41" holes
	5880-5898'	38 holes	.41" holes
	5902-5908'	14 holes	.41" holes
	5918-5934'	34 holes	.41" holes
	5938-5948'	22 holes	.41" holes
	5962-5968'	14 holes	.41" holes
Wolfcamp	5398-5404'	14 holes	.41" holes
	5428-5438'	22 holes	.41" holes
	5466-5474'	18 holes	.41" holes
Cisco	5682-5704'	88 holes	.41" holes

27. Acid, shot, Fracture, Cement Squeeze, etc.

Depth Interval	Amount and Kind of Material Used
5980-5990'	Cement Squeeze with 200 sxs RFCA 10-2 + D 5-3 (wt 14.2, yld 1.6)
5880-5968'	Spot 100 gals 20% IC HCL. Acidize with 3000 gals IC HCL + 200 balls.
5398-5474'	Spot 100 gals 15% IC HCL Acidize with 2400 gals 15% IC HCL + 81 balls
5682-5704'	Spot 50 gals 15% IC HCL Acidize with 2200 gals 15% IC HCL