

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 South First, Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103
Revised March 25, 1999

WELL API NO.

30-005-63307

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

VA-2069

7. Lease Name or Unit Agreement Name:

Handicapper AWI State

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☒ Other ☐

2. Name of Operator

Yates Petroleum Corporation

3. Address of Operator

105 S. 4th Street Artesia, NM 88210

7. Well No.

#1

8. Pool name or Wildcat

Undesignated Foor Ranch
Pre-Permian

4. Well Location

Unit Letter **B** : **660** feet from the **North** line and **1980** feet from the **East** line

Section **3** Township **10S** Range **26E** NMPM **Chaves** County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

3821' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

MULTIPLE
COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING
CASING ☐

COMMENCE DRILLING OPNS. ☒

PLUG AND
ABANDONMENT ☐

CASING TEST AND
CEMENT JOB ☐

OTHER: ☐

Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

12/1/00 - Spud 20" conductor hole at 11:15 AM. Set 40' of 16" conductor pipe, cemented to surface.

12/9/00 - Resumed drilling with rotary tool of 12-1/4" hole at 5:30 AM.

12/10/00 - Reached TD of surface hole at 1110' at 6:00 AM.

Ran 28 joints (1110.44') 8-5/8" 24# J-55 casing set at 1110'. Texas pattern guide shoe set at 1108'. Insert float set at 1066.17'. Cemented with 500 sxs 35:65 Poz C with 6% D20 + 2% S1 + .25 pps D29 (yld 1.99, wt 12.6). Tailed in with 200 sxs C + 2% S1 (yld 1.32, wt 14.8). PD at 3:00 PM. Bumped plug to 966#, held OK. Circ 56 sxs. WOC.

12/11/00 - Drilled out at 12:00 PM. WOC 21 hours. Reduced hole to 7-7/8" and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Susan Herpin

TITLE

Engineering Technician

DATE

January 4, 2002

Type or print name

Susan Herpin

Telephone No. 505-748-1471

(This space for State use)

ORIGINAL SIGNED BY TIM W. GUM
DISTRICT II SUPERVISOR

APPROVED BY

[Signature]

TITLE

DATE

Conditions of approval, if any:

JAN 11 2002