

Submit 3 Copies To Appropriate District
Office
District I
1425 N. Fourth St., Hobbs, NM 88240
District II
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103
Revised March 25, 1999

WELL APPLICANT
NAME: [REDACTED]
5. Indicate Type of Lease
STATE ☒ FEE ☐
6. State Oil & Gas Lease No.
20904
7. Lease Name or Unit Agreement
Name:
Western
8. Well No.
3
9. Pool name or Wildcat
Pecos Slope Abo
10. Elevation (Show whether DR, RKB, RT, GR, etc.)
3827' GR

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS.)

1. Type of Well:
Oil Well ☐ Gas Well ☒ Other ☐
2. Name of Operator
Yates Petroleum Corporation
3. Address of Operator
105 South Fourth Street, Artesia, NM 88210 505-748-1471

4. Well Location
Unit Letter N : 660 feet from the S line and 1500 feet from the W line
Section 30 Township 6S Range 25E NMPM Chaves County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)
3827' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:
PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐
OTHER: ☐
SUBSEQUENT REPORT OF:
REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

- 01/08/01 Spud well at 12:01 a.m.
01/10/01 Drill 14-3/4" hole to 945'. Ran 21 jts 11 3/4" 42# H-40 casing and set at 945'. Cement w/ 500 sx 35:65:6 Class "C" + 2% CaCl2 + 1/8#/sx Polyflake and 200 sx Class "C" + 2% CaCl2. Circ 46 sx. WOC 18 hrs. Test csg to 1000 psi for 15 min. Held good. Drill out w/ 11" bit.
01/15/01 Drill 11" hole to 1692'. Ran 40 jts 8 5/8" 24# casing and set @ 1692'. Cement w/ 250 sx "c" + 2% CaCl2. Est top of cement at 1550'. WOC 18 hrs. Test csg to 1500 psi for 15 min. Held good. Drill out with 7 7/8" bit.
01/20/01 TD 7 7/8" hole at 4050'.
01/22/01 Ran 20 jts 4 1/2" 10.5# SB and 76 jts 4 1/2" 10.5# J-55 casing and set at 4050'. Cement w/ 350 sx Pecos Valley Lite + 4 pps D-42 + 1 pps D-42 + 1 pps D-44 + 2/10% D-65 + 3/10% D-167 + .2% D-46 + .15# D-13. Est top of cement @ 2900'.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Donna Clack TITLE Operations Technician DATE 8-08-01

Type or print name Donna Clack Telephone No. 505-748-1471

(This space for State use)

APPROVED BY TIM W. GUM TITLE DISTRICT II SUPERVISOR DATE AUG 12 2001

Conditions of approval, if any: