			cis	ř	
Submit 3 Copies To Appropriate District	es To Appropriate District State of New Mexico			Form C-103	
Office <u>District I</u>	Energy, Minerals and N		WELL API NO.	Revised March 25, 1999	
1625 N. French Dr., Hobbs, NM 88240 District II				•	
811 South First, Artesia, NM 88210 District III	ia, NM 88210 OIL CONSERVATION DIVISION 1220 South St. Francis Dr.			f Lease	
1000 Rio Brazos Rd., Aztec. NM 87410 Santa Fe NM 87505			STATE X 6. State Oil & Ga		
1220 S. St. Francis Dr., Santa Fe, NM			6. State Off & Ga	.S Lease NO.	
87505 SUNDRY NOTICES AND REPORTS ON WELLS				Unit Agreement Name:	
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)			Horizon "AWH" State		
1. Type of Well: Oil Well Gas Well X	Other	A 19			
Oil Well Gas Well X   2. Name of Operator			7. Well No.		
Yates Petroleum Corporation /			#1		
3. Address of Operator 105 S. 4th Street Artesia, NM 88210			8. Pool name or	Wildcat <b>Pre-Permian</b>	
105 S. 4 <sup>th</sup> Street Artesi	a, NM 88210		FOOI RUNCI	rre-rennian	
4. Well Location					
Unit Letter A: 1200 feet from the North line and 660 feet from the East line					
Section 16	Township <b>9S</b> Rar	1ge <b>26E</b>	NMPM Chaves	s County	
10. Elevation (Show whether DR, RKB, RT, GR, etc.)					
3768' GR					
11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data     NOTICE OF INTENTION TO:   SUBSEQUENT REPORT OF:					
	CHANGE PLANS				
		-	COMMENCE DRILLING OPNS. ABANDONMENT		
	COMPLETION	CEMENT JOB	CEMENT JOB		
			OTHER: Set production casing, cement		
Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.					
1/20/01 – Ran 153 jts (6383.81') casing set at 6380' as follows:					
53 jts 5-1/2" 15.5# SB (2183.74') 100 jts 5-1/2" 15.5# Varn (4200.07')					
Float shoe set at 6380'. Float collar set at 6335.58'. Bottom marker set at 4198.28'.					
Cemented with 500 sxs Pecos Valley Lite with 1 pps D44, 4 pps D24, .2% D65, .3% D167, .2% D46, .15% D13 (yld					
1.42, wt 13). PD at 10:15 PM. Bumped plug to 1520 psi for 5 mins. Had to wash down approximately 20', circulate for 1 hour after on bottom with casing.					
Good circulation throughout job.					
Notified Artesia OCD Jerry Tye of operations 1:45 PM.					
1/21/01 - Released rig at 2:15	βAM.				
I hereby certify that the information	n above is true and complete t	o the best of my knowl	edge and belief.		
SIGNATURE	., . <u>(</u> TIT)	LE <u>Engineering</u>	<b>Technician</b> _DA	ATE <b>August 27, 2001</b>	
Type or print name Susan Herpin Telephone No. 505-748-1471					
(This space for State use)	ORIGINAL SIGNED BY T			AUG 2 9 2001	
APPPROVED BY	DISTRICT II SUPERVISO	LE		DATE	

Conditions of approval, if any: