			c15	1 N)
Submit 3 Copies To Appropriate District State of New Mexico			ΑΑ	Form C-103
Office District I	Energy, Minerals and Nat	ural Resources		Revised March 25, 1999
1625 N. French Dr., Hobbs, NM 88240			WELL API NO.	
District II 811 South First, Artesia, NM 88210	88210 OIL CONSERVATION DIVISION		30-005-63318	
<u>District III</u> 1000 Rio Brazos Rd., Aztec, NM 87410			5. Indicate Type of STATE	T Lease
District IV Santa Fe, NM 8/505		6. State Oil & G		
1220 S. St. Francis Dr., Santa Fe, NM 87505			VA-2059	
SUNDRY NOTICES AND REPORTS ON WELLS			7. Lease Name or	Unit Agreement Name:
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR THE				
PROPOSALS.)		Keno AWK	State	
1. Type of Well:		A TON		
Oil Well Gas Well X 2. Name of Operator	Other / / S	10 0001	7. Well No.	
			#2	
3. Address of Operator			8. Pool name or Wildcat	
105 S. 4 th Street Artesi	ia, NM 88210 \v_	ANILOIA AS	Wildcat Pre	e Permian
4. Well Location				
Unit Letter J: 1980 feet from the South line and 1980 feet from the East line				
Section 4	Township 10S Range	26E	MPM Chaves	County
	10. Elevation (Show whether L			county
3798' GR				
11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data				
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:				
	PLUG AND ABANDON		к	ALTERING CASING
	CHANGE PLANS COMMENCE DR		LLING OPNS. X	PLUG AND ABANDONMENT
PULL OR ALTER CASING	MULTIPLE COMPLETION	CASING TEST A		
OTHER:		OTHER:		
12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion				
or recompilation. 11/28-12/3/00 - Build location.				
12/04/00 – Spud 1:30 PM with 20" hole. Set 40' of 16" conductor, cement to surface. Notified Mike Stubblefield of OCD.				
12/8/00 – Resumed drilling at 10:45 PM, 12-1/4" hole. Notified Artesia OCD of operations on 12/9/00. 12/10/00 – Reached TD of surface hole 9:30 PM. Ran 26 joints of 8-5/8" 24# J-55 (1107.48') casing set at1108'.				
Texas Pattern Notched guide shoe set at 1106'. Insert float set at 1063.55'. Cemented with 500 sxs 35:65:6 C + 6% D20 + 2%				
S1 + ¼#/sx D29 (yld 1.99, wt 12.6). Tailed in with 200 sxs C + 2% S1 (yld 1.32, wt 14.8). 12/11/00 - PD at 4:00 AM . Bumped plug to 880 psi, held OK. Circulated 48 sxs. WOC. Notified Artesia OCD (answering				
service) of operations. Drilled ou				
drilling.				
1/1/01 - Reached TD of 6430' at 2:45 AM. Logging well. Loggers TD 6404'.				
1/3/01 – Ran 156 jts casing set at 6414' as follows: 49 joints 5-1/2" 15.5# SB (2001.27'); 107 jts 5-1/2" 15.5# MV (4436') . Set Regular guide shoe at 6430', Float collar at 6371.5', Bottom marker 5929.71', Top marker 4412.73'. Cemented with 650 sxs				
Pecos Valley Lites, 4 pps D42, 1 pps D44, .2% D65, .3% D167, .2% D46, .15% D13 (yld 1.42, wt 13.0). PD at 6:30 PM. Bump plug				
to 1900 psi for 4 mins., held OK. Notified Mike Stubblefield of OCD before starting pipe.				
Released rig 10:00 PM 1/3/01. I hereby certify that the information above is true and complete to the best of my knowledge and belief.				
SIGNATURE Man H	ipenTITLE	Engineering	<u>Technician</u> DA	TE August 16, 2001
Type or print name Sysan He	rpin		Telephone	No. 505-748-1471
(This space for State use) ORIGI	NAL SIGNED BY TIM W. GUN	A.	*	
APPPROVED BY	ICT II SUPERVISOR			AUG 1 7 2001
Conditions of approval, if any:				