by Appropriate Distribution Energy, Allertas Bio Allian Resolutes Department Member 1-0-00 Member 1-0-00 DETRICT OIL CONSERVATION DIVISION P.O. Box 2088 Santa Fe, New Mexico 87504-2088 Santa Fe, New Mexico 87504-2088 Santa Fe, New Mexico 87504-2088 DETRICT SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM PCR PROPOSALS TO DRUCH PROPOSALS TO ARULE AT DEPENDENCE PROPOSALS TO DRUCH PROPOSALS TO DRUCH PROPOSALS AND THE PROPOSALS TO DRUCH PROPOSALS AND THE PROPOSALS AND				
F0. Do 198, Hobe, NM 4300 P.O. Box 2088 30-005-63323 F0. Do 2088 Santa FC, New Mexico 87504-2088 3 toticus Type of Low F0. Do Ref DD, Ansie, NM 8810 Santa FC, New Mexico 87504-2088 5 toticus Type of Low F0. Do Rot USE THE CELL Santa FC, New Mexico 87504-2088 5 toticus Type of Low F0. Do NOT USE THE SOM CONTROPOSALS TO PERIOR SON WELLS 6 Sant Ol & Gas Lesse No. F0. Do NOT USE THE SOM CONTROPOSALS TO PERIOR PARENCE ALLO P	- Submit 3 Copies to Appropriate District Office			
District III Conserve DD, Ameria, NM 88210 Santa FC, New MExico 87504-2088 I indust Type of Lew STATE I indust Type of Lew STATE reg State STATE reg State STATE reg State STATE reg State State State reg State State reg State S	<u>DISTRICT I</u> P.O. Box 1980, Hobbs, NM 83240			
DSTRUCTION 6. Sum ON & Gai Lame No. SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM POR IPOROSALS TO DRILL OR TO DEEPEN CR FUE BACK TO A DEFERENT RELEVOR. USE APPROVED. USE APPROVED TO THE SOUTH PAPOPOSALS (PLC) 7. Lease Name of Unit Agreement Name Type of Well Wall (Sill) Once of General Control (Sill) 8. Well No. Type of Well Market of Operation Sacta SA Com 14 Name of Operation Sacta SA Com 14 14 Address of Operation Sacta SA Com 14 14 Valid Costie Sacta SA Com 14 14 Address of Operation Sacta SA Com 14 14 Valid Costie Sacta SA Com 14 14 Address of Operation Sacta SA Com 14 14 Valid Costie Sacta SA Com 14 14 Valid Costie Sacta SA Com 14 14	DISTRICT II P.O. Drawer DD, Artesia, NM 88210	6 Indiante Time of Lesse		
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TOA DIFFERENT RESERVOR. USE "APPLICATION FOR PERIOSTATISTS" 7. Less Name of Usit Agreement Name 'Type of Weil Weil I	DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 8741)			
(DO NOT USE THIS FORM FOR PROPOSALS TO DIFLIC OR TO DEEPEN OR PLUG BACK TOA DIFFERENT RESERVOR. USE APPLICATION FOR PERINTIA 1936 7. Lease Name of Usit Agreement Name 'Type of Neul		TIOFS AND DEDOUTS ON WELL		
Will Gorado Will State and Operator Sacra SA Com Andread Operator Socra SA Com A Welk No. Addread Operator Socra SA Com A Addread Operator Socra Sacra SA Com A Addread Operator Socra Sacra SA Com A Addread Operator Socra Sacra SA Com H Lossion Socra Sacra SA Com H Unit Letter K : : 1980 Feet From The South Peccos Slope Abo Socra 19 Towership 65 Range 26E NMEM Chaves Comy Unit Letter K : : : : : : : : : : : : : : : : : : :	(DO NOT USE THIS FORM FOR PF DIFFERENT RESE (FORM)	ROPOSALS TO DRILL OR TO DEEPEN (RVOIR. USE "APPLICATION FOR PER	0R PLUG BACK TO A	7. Lease Name or Unit Agreement Name
YATES PETROLEUM CORPORATION 14 37. Addies of Operator 14 105 South 4th St., Artesia, NM 88210 9. Pool sume of Wided 105 South 4th St., Artesia, NM 88210 9. Pool sume of Wided 105 South 4th St., Artesia, NM 88210 9. Pool sume of Wided 105 South 4th St., Artesia, NM 88210 9. Pool sume of Wided 11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: 3723' GR 11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: REMEDIAL WORK PLUG AND ABANDON CHARGE PLANS COMMERCE OFLING OPNS. VIL ON ALTER CASING CHARGE PLANS OTHER Surface CaSing & cement VIL ON ALTER CASING COMMERCE OFLING OPNS. 12 Decribe Proposed or Completed Operations (Clearly state all perioder data), and give perioder data: ficulating etimated date of staring any proposed words 58 RULE 100. Spudded a 20" hole with rat hole machine set 12:30 PM 8-4-2001. Drilled to 40'. Set 40' of 16" conductor pipe. Cemented to surface. NOTE: Notified OCD-Artesia of operations. Resumed drilling a 14-3/4" hole with rotary tools at 9!45 AM 8-13-2001. TD 917'. Reached TD at 8:45 PM 8-14-2001. Ran 116 of 11-3/42.f		OTHER 0	Nou B	Sacra SA Com
3. Addies of Operator 9. Fost Bind & Videal 105 South 4th St., Artesia, NM 88210 44. 54 Pecces Slope Abo 4. Well Lestion 1980 Feet From The South Pecces Slope Abo 4. Well Lestion 19 Township 65 Range 26E NMPM Chaves Construction Section 19 Township 65 Range 26E NMPM Chaves Construction 10 Different Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: EMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDON CAMMENCE DRILLING OPNS. PLUG AND ABANDON/ENT VULIOR ALTER CASING OTHER: OTHER: Spuid, conductor, resume drilling, Surflace (casing 4 comment) Surflace (casing 4 comment) 12 Describe Proposed or Completed Operations (Clearly state all perioses dealls, and give perioset date, including estimated date of staring any proposet work, SEE RUE 1103. Surflace (casing 4 comment) Set 40' 0 f16" conductor pipe. Cemented to surface. NOTE: Notified 0CD-Attesia of operations. Reserved of 11-3/4" 42# (917.33') of casing set at 917'. Insert float set at 852'. The sack folly flake (yiciell 1.99, weight 12.6).	Name of Operator YATES PETROLEUM CORPO	RATION - 19 OC	TECEIVED TO	
Will Lestion Usit Letter k 1980 Feet From The Liter Section 19 Township 6S Range 26E NMPM Chayes Control 3723' GR 3723' GR Control Control Control Control State RT, GR, etc.) 3723' GR Control Contro C	-		ARTEC	
Unit Letter K : 1980 Feet From The Line Section 19 Towratip 6S Rage 26E NMFM Chayes Covery 10. Elevation (Show Wither DF, R&R, RT, GR, etc.) 3723' GR 3723' GR		tesia, NM 88210 A	-01A N/	Pecos Slope Abo
Section 10 Elevalion (Show whether DF, REB, RT, GR, etc.) 3723' CR 3723' CR 11. Check & Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: FREFORM REMEDIAL WORK PLUG AND ABANDON CHANGE PLUS COMMENCE DRILLING OPNS. PLUG AND ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT CASING TEST AND CEMENT JOB COMMENCE DRILLING OPNS. OTHER: Spud. conductor, resume drilling, Sutface Casing Casing test may proposed Syndded a 20° hole with rat hole machine at 12:30 PM 8-4-2001. Drilled to 40'. Set 40' of 16° conductor pipe. Cemented to surface. NOTE: Notified OCD-Artesia of operations. Resumed drilling a 14-3/4" hole with rotary tools at 9:45 AM 8-13-2001. TD 917'. Reached TD at 8:45 PM 8-14-2001. Ran 21 joints of 11-3/4" 42# (917.33') of casing set at 917'. 1-Texas Pattern notched guide shoe set at 917'. Insert float set at 852'. Cemented with 450 sacks "C" (65-35-6). 5# fsack gilsonite, 2% CaCl2 and 1/8#/ sack polyflake (yield 1.99, weight 12.6). Tailed in with 200 sacks "C" and 2% CaCl2 (yield 1.32, weight 14.8). PD 9:30 AM 8-15-2001. Bumped plug tos 555	17 I	980 Feet From The South	Line 198	0 Feet From The <u>West</u> Line
10. Elevation (Show watcher DP, RKB, RT, GR, dc.) 3723' GR 11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING CMARKEY JABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONSKENT VULL OR ALTER CASING CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONSKENT VULL OR ALTER CASING CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONSKENT VULL OR ALTER CASING OTHER: Spud., conductor, resume drilling, Starting comment data, including astimated data of starting any proposed VOMUS SER RULE 103. Spudded 20" hole with rat hole machine at 12:30 PM 8-4-2001. Drilled to 40'. Set 40' of 16" conductor pipe. Cemented to surface. NOTE: Notified OCD-Artesia of operations. Resumed drilling a 14-3/4" hole with rotary tools at 9:45 AM 8-13-2001. TD 917'. Insert float set at 92'. Cemented with 450 sacks "C" (65-35-60), 5#/sack gilsonite, 2% CaCl2 and 1/8#/ sack polyflake (yield 1.99, weight 12.6). Tailed in with 200 sacks "C" and 2% CaCl2 (yiell 1.32, weight 12.6). Tailed in with 200 sacks "C" and 2% CaCl2 (yiell 1.32, weight 12.6). Tailed in with 200 sacks "C" and 2% CaCl2 (yiell 1.32, weight 12.6). Tailed in with 200 sacks "C" and 2% CaCl2 (yiell 1.99, weight 12.6). Tailed in with 200 sacks "C" and 2% CaC	Sertion 19	Township 6S Rat		NMPM Chaves County
II. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: ERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING CMMENCE DRILLING OPNS. PLUG AND ABANDONMENT CASING TEST AND CEMENT JOB VULL OR ALTER CASING OTHER: Spud, conductor, resume drilling, K OTHER: OTHER: Spud, conductor, resume drilling, K 12. Describe Proposed or Completed Cystations (Clearly state all periment deails, and give periment deails, including stimuted date of staring any proposed work) SEE RULE 1103. Spudded a 20" hole with rat hole machine at 12:30 PM 8-4-2001. Drilled to 40'. Set 40' of 16" conductor pipe. Cemented to surface. NOTE: Notified OCD-Artesia of operations. Resumed drilling a 14-3/4" hole with rotary tools at 9:45 AM 8-13-2001. Trilled to 40'. Set 40' TD 917'. Reached TD at 8:45 PM 8-14-2001. Ran 21 joints of 11-3/4" 42# (917.33') of casing set at 917'. Insert float set at 52'. Cemented with 450 sacks (C'G (55-35-6), 5#/sack gilsonite, 2% Cal2 and 1/8#/ Sack polyflake (yield 1.99, weight 12.6). Tailed in with 200 sacks "C" and 2% Cal2 and 1/8#/ sack s. WOC. Cut of f and welded on flow nipple. Drilled out at 3:30 AM 8-16-2001. WOC 18 hours. Reduced hole to 11". Resumed drilling. Reduced 11" hole to 7-7/8" hole at 1525'.		10. Elevation (Show whether I	OF, RKB, RT, GR, etc.)	
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: EMPORABLY ABANDON PLUG AND ABANDON REMEDIAL WORK ALTERING CASING EMPORABILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT ULL OR ALTER CASING CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT ULL OR ALTER CASING CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT ULL OR ALTER CASING CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT ULL OR ALTER CASING CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT ULL OR ALTER CASING CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT ULL OR ALTER CASING CHANGE PLANS CASING TEST AND CEMENT JOB CASING TEST AND CEMENT JOB ULL OR ALTER CASING CHANGE PLANS CASING TEST AND CEMENT JOB CASING TEST AND CEMENT JOB ULL OR ALTER CASING CHANGE PLANS CASING TEST AND CEMENT JOB CASING TEST AND CEMENT JOB ULL OR ALTER CASING CHEMENT JOB OTHER Spud. CASING TEST AND CEMENT JOB 12 Describe Proposed or Complete Commende to Surface. NOT IS EST AND CEMENT JASE CASING TEST AND CEMENT JASE 12 Descrid sta				
ERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING EMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT ULL OR ALTER CASING CHANGE PLANS CASING TEST AND CEMENT JOB PLUG AND ABANDONMENT ULL OR ALTER CASING OTHER: Spud. conductor, resume drilling, K K THER: OTHER: Spud. conductor, resume drilling, K Spudded a 20" hole with rat hole machine at 12:30 PM 8-4-2001. Drilled to 40'. Set 40' of 16" conductor pipe. Cemented to surface. NOTE: Notified OCD-Artesia of operations. Resumed drilling a 14-3/4" hole with rotary tools at 9:45 AM 8-13-2001. TD 917'. Reached TD at 8:45 PM 8-14-2001. Ran 21 joints of 11-3/4" 42# (917.33') of casing set at 917'. 1-Texas Pattern notched guide shoe set at 917'. Insert float set at 852'. Cemented with 450 sacks "C" (65-35-6), 5#/sack gilsonite, 2Z Cacl2 and 1/8#/ sack polyflake (yield 1.99, weight 12.6). Tailed in with 200 sacks "C" and 2% Cacl2 (yield 1.32, weight 14.8). PD 9:30 AM 8-15-2001. Bumped plug to 805 psi, 0K. Circulated 87 sacks. WOC. Cut off and welded on flow nipple. Drilled out at 3:30 AM 8-16-2001. WOC 18 hours. Reduced hole to 11". Resumed drilling. Reduced 11" hole to 7-7/8" hole at 1525'. Iherby centry two fe information boote trab and complete to the best of my throwtoge and belid.			Nature of Notice, R	eport, or Other Data
EMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT EMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT ULL OR ALTER CASING CASING TEST AND CEMENT JOB CASING TEST AND CEMENT JOB Image: Comment of the superiment data is including estimated date of starting any proposed THER: OTHER: Spud. conductor, resume drilling, K Spudded a 20" hole with rat hole machine vat 12:30 PM 8-4-2001. Drilled to 40'. Set 40' of 16" conductor pipe. Cemented to surface. NOTE: Notified OCD-Artesia of operations. Resumed drilling a 14-3/4" hole with rotary tools at 9:45 AM 8-13-2001. TD 917'. Reached TD at 8:45 PM 8-14-2001. Ran 21 joints of 11-3/4" 42# (917.33') of casing set at 917'. 1-Texas Pattern notched guide shoe set at 917'. Insert float set at 852'. Cemented with 450 sacks "C" (65-35-6), 5#/sack gilsonite, 2% CaCl2 and 1/8#/ sack polyfiake (yield 1.99, weight 12.6). Tailed in with 200 sacks "C" and 2% CaCl2 (yield 1.32, weight 14.8). PD 9:30 AM 8-15-2001. Bumped plug to 805 psi, 0K. Circulated 87 sacks. WOC. Cut off and welded on flow nipple. Drilled out at 3:30 AM 8-16-2001. WOC 18 hours. Reduced hole to 11". Resumed drilling. Reduced 11" hole to 7-7/8" hole at 1525'. Interdy rentry fuel Mov 16 2001 ORIGINAL SIGNED BY TIM W. GUM NOV 1 6 2001 ORIGINAL SIGNED BY TIM W. GUM NOV 1 6 2001	NOTICE OF IN	ITENTION TO:	SUB	SEQUENT REPORT OF:
CASING TEST AND CEMENT JOB ULL OR ALTER CASING UTHER: CASING TEST AND CEMENT JOB OTHER: OTHER: OTHER: OTHER: OTHER: OTHER: Spudded a 20" hole with rat hole machine at 12:30 PM 8-4-2001. Drilled to 40'. Set 40' of 16" conductor pipe. Cemented to surface. NOTE: Notified 0CD-Artesia of operations. Resumed drilling a 14-3/4" hole with rotary tools at 9:45 AM 8-13-2001. TD 917'. Reached TD at 8:45 PM 8-14-2001. Ran 21 joints of 11-3/4" 42# (917.33') of casing set at 917'. I-Texas Pattern notched guide shoe set at 917'. Insert float set at 852'. Cemented with 450 sacks "C" (65-35-6). sack polyflake (yield 1.99, weight 12.6). Tailed in with 200 sacks "C" and 2% CaCl2 (yield 1.32, weight 14.8). PD 9:30 AM 8-15-2001. Bumped plug to 805 psi, 0K. Circulated 87 sacks. WOC. Cut off and welded on flow nipple. Drilled out at 3:30 AM 8-16-2001. WOC 18 hours. Reduced hole to 11". Resumed drilling. Reduced 11" hole to 7-7/8" hole at 1525'. Iherdry cently by the Information about, for bast complete to the best of my toowidge and belief. TYPE OR FRINT NAME NOV 16 2001 <			REMEDIAL WORK	
OTHER: OTHER: Spud, conductor, resume drilling, X DTHER: Surface casing & cement X 12 Desche Proposed or Completed Cperations (Clearly state all periment details, and give periment datas, including estimated date of starting any proposed X work) SEE RULE 103. Spudded a 20" hole with rat hole machine at 12:30 PM 8-4-2001. Drilled to 40'. Set 40' of 16" conductor pipe. Cemented to surface. NOTE: Notified OCD-Artesia of operations. Resumed drilling a 14-3/4" hole with rotary tools at 9:45 AM 8-13-2001. TD 917'. Reached TD at 8:45 PM 8-14-2001. Ran 21 joints of 11-3/4" 42# (917.33') of casing set at 917'. 1-Texas Pattern notched guide shoe set at 917'. Insert float set at 852'. Cemented with 450 sacks "C" (65-35-6), 5#/sack gilsonite, 2% caCl2 and 1/8#/ sack polyflake (yield 1.99, weight 12.6). Tailed in with 200 sacks "C" and 2% caCl2 (yield 1.32, weight 14.8). PD 9:30 AM 8-15-2001. Bumped plug to 805 psi, 0K. Circulated 87 sacks. WOC. Cut off and welded on flow nipple. Drilled out at 3:30 AM 8-16-2001. WOC 18 hours. Reduced hole to 11". Resumed drilling. Reduced 11" hole to 7-7/8" hole at 1525'. Iherdry certify the the information mode from bad complete to the best of my travelege and belief. YMMAR THE ORIGINAL SIGNED BY TIM W. GUM DISTRICT II SUPERVISOR NOV 1 6 2001			COMMENCE DRILLING	
Surface casing & cement 12 Describe Proposed or Completed Operations (Clearly state all periment datals, and give periment dates, including estimated date of starting any proposed work) SEE RULE 103. Spudded a 20" hole with rat hole machine at 12:30 PM 8-4-2001. Drilled to 40'. Set 40' of 16" conductor pipe. Cemented to surface. NOTE: Notified OCD-Artesia of operations. Resumed drilling a 14-3/4" hole with rotary tools at 9:45 AM 8-13-2001. TD 917'. Reached TD at 8:45 PM 8-14-2001. Ran 21 joints of 11-3/4" 42# (917.33') of casing set at 917'. 1-Texas Pattern notched guide shoe set at 917'. Insert float set at 852'. Cemented with 450 sacks "C" (65-35-6), 5#/sack gilsonite, 2% CaCl2 and 1/8#/ sack polyflake (yield 1.99, weight 12.6). Tailed in with 200 sacks "C" and 2% CaCl2 (yield 1.32, weight 14.8). PD 9:30 AM 8-15-2001. Bumped plug to 805 psi, 0K. Circulated 87 sacks. WOC. Cut off and welded on flow nipple. Drilled out at 3:30 AM 8-16-2001. WOR 18 hours. Reduced hole to 11". Resumed drilling. Reduced 11" hole to 7-7/8" hole at 1525'. Interment Operations Technician Date Oct. 30, 2001 TTHE OPERATIONS Technician Date Oct. 30, 2001 THE Date Operations Technician Date Oct. 30, 2001 THE Date				
work) SEE RULE 103. Spudded a 20" hole with rat hole machine at 12:30 PM 8-4-2001. Drilled to 40'. Set 40' of 16" conductor pipe. Cemented to surface. NOTE: Notified 0CD-Artesia of operations. Resumed drilling a 14-3/4" hole with rotary tools at 9:45 AM 8-13-2001. TD 917'. Reached TD at 8:45 PM 8-14-2001. Ran 21 joints of 11-3/4" 42# (917.33') of casing set at 917'. 1-Texas Pattern notched guide shoe set at 917'. Insert float set at 852'. Cemented with 450 sacks "C" (65-35-6), 5#/sack gilsonite, 2% CaCl2 and 1/8#/ sack polyflake (yield 1.99, weight 12.6). Tailed in with 200 sacks "C" and 2% CaCl2 (yield 1.32, weight 14.8). PD 9:30 AM 8-15-2001. Bumped plug to 805 psi, OK. Circulated 87 sacks. WOC. Cut off and welded on flow nipple. Drilled out at 3:30 AM 8-16-2001. WOC 18 hours. Reduced hole to 11". Resumed drilling. Reduced 11" hole to 7-7/8" hole at 1525'. I hereby certify the be information above f tob and complete to the best of my throwiedge and belief. SKONATURE Mathematican above f tob and complete to the best of my throwiedge and belief. MOV 1 6 2001 Chia space for State Use) ORIGINAL SIGNED BY TIM W. GUM DISTRICT II SUPERVISOR NOV 1 6 2001 ATROVED BY TITE			surface	casing & cement
of 16" conductor pipe. Cemented to surface. NOTE: Notified OCD-Artesia of operations. Resumed drilling a 14-3/4" hole with rotary tools at 9:45 AM 8-13-2001. TD 917'. Reached TD at 8:45 PM 8-14-2001. Ran 21 joints of 11-3/4" 42# (917.33') of casing set at 917'. 1-Texas Pattern notched guide shoe set at 917'. Insert float set at 852'. Cemented with 450 sacks "C" (65-35-6), 5#/sack gilsonite, 2% CaCl2 and 1/8#/ sack polyflake (yield 1.99, weight 12.6). Tailed in with 200 sacks "C" and 2% CaCl2 (yield 1.32, weight 14.8). PD 9:30 AM 8-15-2001. Bumped plug to 805 psi, OK. Circulated 87 sacks. WOC. Cut off and welded on flow nipple. Drilled out at 3:30 AM 8-16-2001. WOC 18 hours. Reduced hole to 11". Resumed drilling. Reduced 11" hole to 7-7/8" hole at 1525'. I hereby certify that the information above in the and complete to the best of my knowledge and belief. SIONATURE	work) SEE RULE 1103.			
TD 917'. Reached TD at 8:45 PM 8-14-2001. Ran 21 joints of 11-3/4" 42# (917.33') of casing set at 917'. 1-Texas Pattern notched guide shoe set at 917'. Insert float set at 852'. Cemented with 450 sacks "C" (65-35-6), 5#/sack gilsonite, 2% CaCl2 and 1/8#/ sack polyflake (yield 1.99, weight 12.6). Tailed in with 200 sacks "C" and 2% CaCl2 (yield 1.32, weight 14.8). PD 9:30 AM 8-15-2001. Bumped plug to 805 psi, OK. Circulated 87 sacks. WOC. Cut off and welded on flow nipple. Drilled out at 3:30 AM 8-16-2001. WOC 18 hours. Reduced hole to 11". Resumed drilling. Reduced 11" hole to 7-7/8" hole at 1525'. I hereby certify that the information above, i the and complete to the best of my knowledge and belief. SIONATURE	of 16" conductor pip	e. Cemented to surface.	. NOTE: Notif	ied OCD-Artesia of operations.
I hereby certify that the information above is the and complete to the best of my knowledge and belief. SHONATURE ITTLE Operations Technician TYPE OR PRINT NAME Rusty Klein Date (This space for State Use) ORIGINAL SIGNED BY TIM W. GUM DISTRICT II SUPERVISOR NOV 1 6 2001 APPROVED BY	TD 917'. Reached TI casing set at 917'. at 852'. Cemented v sack polyflake (yiel (yield 1.32, weight 87 sacks. WOC. Cut) at 8:45 PM 8-14-2001. 1-Texas Pattern notched with 450 sacks "C" (65-3) 14.8). PD 9:30 AM 8-15- c off and welded on flow	Ran 21 joints d guide shoe se 5-6), 5#/sack g Tailed in with -2001. Bumped nipple. Drill	of 11-3/4" 42# (917.33') of t at 917'. Insert float set ilsonite, 2% CaCl2 and 1/8#/ 200 sacks "C" and 2% CaCl2 plug to 805 psi, OK. Circulated
SIGNATURE Operations Technician DATE Oct. 30, 2001 TYPE OR PRINT NAME Rusty Klein TTHE OPERATIONS Technician DATE OCt. 30, 2001 TYPE OR PRINT NAME Rusty Klein TTHE OPERATIONS Technician TTHE OCt. 30, 2001 TTHE OPERATIONS Technician THEPHONE NO. 505/748-14 ORIGINAL SIGNED BY TIM W. GUM DISTRICT II SUPERVISOR APPROVED BY TTHE	Ω	1	haliof	
SUMATORS TELEPHONE NO. 505/748-14 TYPE OR PRINT NAME Rusty Klein ORIGINAL SIGNED BY TIM W. GUM NOV 16 2081 ORIGINAL SIGNED BY TIM W. GUM NOV 16 2081 APPROVED BY TITLE	A lister T	TUE and complete to the best of my knowledge and	. Operations 7	Technician DATE Oct. 30, 2001
(This space for State Use) ORIGINAL SIGNED BY TIM W. GUM DISTRICT II SUPERVISOR NOV 1 6 2001 APPROVED BY TITLE DATE				тецернские но. 505/748-14
APPROVED BY	A IN		W. GUM	NOV 1 6 2081
		TI	æ	DATE