

CISF
99

DISTRICT I
P.O. Box 1980, Hobbs, NM 83240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-005-63323
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Sacra SA Com
8. Well No. 14
9. Pool name or Wildcat Pecos Slope Abo

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER	2. Name of Operator YATES PETROLEUM CORPORATION
3. Address of Operator 105 South 4th St., Artesia, NM 88210	4. Well Location Unit Letter K : 1980 Feet From The South Line and 1980 Feet From The West Line

Section 19	Township 6S	Range 26E	NMPM	Chaves	County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3723' GR					

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: Production casing & cement <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.
TD 5400'. Reached TD at 8:45 AM 8-26-2001. Ran 127 joints of 4-1/2" 11.6# N-80 casing as follows: 56 joints of 4-1/2" 11.6# N-80 sandblasted (2340.65') and 71 joints of 4-1/2" 11.6# N-80 varnished (3061.19') (Total 5401.84') of casing set at 5400'. Float shoe set at 5400'. Float collar set at 5358'. Bottom marker set at 4234'. Top marker set at 3060'. Cemented with 600 sacks Pecos Valley Lite, 4#/sack D-42, 1#/sack D-44, 2/10% D-65, 3/10% D-167 and .2% D-46 (yield 1.42, weight 13.0). PD 6:00 AM 8-28-2001. Bumped plug to 1900 psi for 4 minutes, OK. WOC. Released rig at 11:00 AM 8-28-2001. NOTE: Notified Van Barton w/OCD-Artesia of operations.

Waiting on completion unit.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.
SIGNATURE Rusty Klein TITLE Operations Technician DATE Oct. 30, 2001
TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-1471
(This space for State Use) ORIGINAL SIGNED BY TIM W. GUM
DISTRICT II SUPERVISOR **NOV 16 2001**

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: