

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
311 South First, Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103
Revised March 25, 1999

WELL APINO.

30-005-63325

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

LG-0563

7. Lease Name or Unit Agreement Name:

Smernoff NL State Com

7. Well No.

#8

8. Pool name or Wildcat

Pecos Slope Abo

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☒ Other ☐

2. Name of Operator

Yates Petroleum Corporation

3. Address of Operator

105 S. 4th Street Artesia, NM 88210

4. Well Location

Unit Letter D : 660 feet from the North line and 660 feet from the West line

Section 1 Township 5S Range 24E NMPM Chaves County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

3937' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETION ☐

OTHER:

☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: set and cement production casing

☐

Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

6/22/01 - Reached TD at 4205' at 11:30 PM.

6/23/01 - Run open hole logs. Loggers TD 4196'

6/24/01 - Ran 96 joints (4205.68') casing set at 4205' as follows:

30 joints 4-1/2" 10.5# J-55 SB (1262.87')

66 joints 4-1/2" 10.5# J-55 MV (2942.81')

Float shoe set at 4205'. Float collar set at 4162.19'. Top marker set at 2942.13'.

Cemented with 340 sxs pecos Valley Lite + 3 pps salt + 4 pps gilsonite + .1% D65 + .4% D167 + .2% D46 (yld 1.45, wt 13). Plug down at 5:30 PM. Bumped plug to 1346 psi for 4 min. Held OK.

Notified Mike Stubblefield with Artesia OCD before starting pipe.

Rig released at 9:30 PM 6/24/01.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Susan Herpin TITLE Engineering Technician DATE December 20, 2001

Type or print name Susan Herpin

Telephone No. 505-748-1471

(This space for State use)

ORIGINAL SIGNED BY TIM W. GUM
DISTRICT II SUPERVISOR

APPROVED BY [Signature] TITLE DISTRICT II SUPERVISOR DATE DEC 28 2001

Conditions of approval, if any: