

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 South First, Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103
Revised March 25, 1999

WELL API NO.
30-005-63330

5. Indicate Type of Lease
STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name:

Johnson II

7. Well No.

#4

8. Pool name or Wildcat

Wildcat PreCambrian

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☒ Other ☐

2. Name of Operator

Yates Petroleum Corporation

3. Address of Operator

105 S. 4th Street Artesia, NM 88210

4. Well Location

Unit Letter **K : 1980** feet from the **South** line and **1980** feet from the **West** line

Section **30** Township **6S** Range **26E** NMPM **Chaves** County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

3704' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

MULTIPLE
COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☒

PLUG AND
ABANDONMENT ☐

CASING TEST AND
CEMENT JOB ☐

OTHER: ☐

Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

4/11/01 - Spudded 20" hole with rathole machine at 11:00 AM. Set 40' of 16" conductor pipe cemented to surface. Notified Artesia OCD of spud on 4/12/01.

4/16/01 - Resume drilling with 14-3/4" hole with rotary tools at 7:30 PM.

4/18/01 - Reached TD of 14-3/4' hole at 914'. Ran 21 jts. (915.37') 11-3/4" 42# HE casing set at 914'. Texas Pattern guide shoe set at 914'. Insert float set at 871.65'. Cemented with 350 sxs 35:65:6 C + 2% CaCl2 + 1/8 pps polyflake (yld 1.99, wt 12.7). Tailed in with 200 sxs C + 2% CaCl2 (yld 1.32, wt 14.8). PD at 5:30 PM. Bumped plug to 630#, held OK. Circ 80 sxs. WOC. Notified Phil Hawkins with OCD at 9:00 AM.

4/19/01 - Drilled out at 12:15 PM. WOC 18 hrs. 45 mins. Reduced hole to 11" and resumed drilling.

4/21/01 - Drilled to 1500'. Circulate hole, no loss. Reduce hole to 7-7/8" and resume drilling.

4/29/01 - Reached TD at 5240' at 10:00 PM.

4/30/01 - Run open hole logs. Logger's TD 5224'.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE *Susan Herpin* TITLE **Engineering Technician** DATE **October 3, 2001**

Type or print name **Susan Herpin**

Telephone No. **505-748-1471**

(This space for State use)

APPROVED BY

**ORIGINAL SIGNED BY TIM W. GUM
DISTRICT II SUPERVISOR**

DATE

OCT 07 2001

Conditions of approval, if any: