

Submit 3 Copies To Appropriate District Office  
District I  
1925 N. French Dr., Hobbs, NM 88240  
District II  
811 South First, Artesia, NM 88210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

Form C-103  
Revised March 25, 1999

WELL API NO.

30-005-63333

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

LG-0567

7. Lease Name or Unit Agreement Name:

Grynberg LZ State

7. Well No.

#5

8. Pool name or Wildcat

Wildcat PreCambrian

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☒ Other ☐

2. Name of Operator

Yates Petroleum Corporation

3. Address of Operator

105 S. 4th Street Artesia, NM 88210

4. Well Location

Unit Letter O : 660 feet from the South line and 1980 feet from the East line

Section 36

Township 5S

Range 24E

NMPM

Chaves

County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

3881' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

REMEDIAL WORK ☐

ALTERING CASING ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETION ☐

CASING TEST AND CEMENT JOB ☐

OTHER:

OTHER: set production casing, cement

☒

Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

7/26/01 - Rigged up pulling unit.

7/27/01 - TIH with bit and scraper. Tag PBTD at 5267'.

7/30/01 - Run CBL. TOC 3050'.

Perf Penn sand 5015-5021' with 36 holes, .42" holes.

7/31/01 - Spot 50 gals 7.5% IC HCL. Acidize perfs 5015-5021' with 600 gals IC HCL. RU swab.

8/2/01 - Set CIBP at 4950' with 35' cement on top.

Perforate Abo 3685-3689', 3697-3700', 3764-3772', 3818-3831', 3844-3848', 1 JSPF, total of 37 holes, .42" holes.

8/7/01 - Spot 500 gals 7.5% IC HCL over Abo perfs. Perforate Abo 3774-3782' with 9 holes, .42".

8/9/01 - Frac Abo perfs 3685-3848' with 96,000 gals 65Q N2 foamed 35# gel and 214,000# 16/30 Brady sand, with 2000 gals 7.5% IC HCL ahead of pad.

8/15/01 - TIH with 2-3/8" tbg and packer. Set packer at 3630'.

8/16/01 - Rig down and move out pulling unit. Turn well to production.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE

Engineering Technician

DATE October 2, 2001

Type or print name

Susan Herpin

Telephone No. 505-748-1471

(This space for State use)

ORIGINAL SIGNED BY TIM W. GUM  
DISTRICT II SUPERVISOR

APPROVED BY

TITLE

DATE

Conditions of approval, if any:

OCT 07 2001