

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240DISTRICT II
P.O. Drawer DD, Artesia, NM 88210DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.
30-005-63334

5. Indicate Type of Lease
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.
LG-0567

7. Lease Name or Unit Agreement Name
Grynberg LZ State

8. Well No.
6

9. Pool name or Wildcat
Wildcat Precambrian

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
3896' GR

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☐ GAS WELL ☒ OTHER ☐

2. Name of Operator
YATES PETROLEUM CORPORATION

3. Address of Operator
105 South 4th St., Artesia, NM 88210

4. Well Location
Unit Letter K : 1980 Feet From The South Line and 1980 Feet From The West Line
Section 36 Township 5S Range 24E NMPM Chaves County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
3896' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>		CASING TEST AND CEMENT JOB <input type="checkbox"/>	
OTHER: <input type="checkbox"/>		OTHER: Production casing and cement <input checked="" type="checkbox"/>	

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 5311'. Reached TD at 10:00 AM 11-5-2001. Ran 125 joints of 4-1/2" 11.6# casing as follows: 11 joints of 4-1/2" 11.6# P-110 sandblasted (481.29'); 33 joints of 4-1/2" 11.6# N-80 sandblasted (1372.62') and 81 joints of 4-1/2" 11.6# N-80 varnished (3459.03') (Total 5312.94') of casing set at 5311'. Float shoe set at 5311'. Float collar set at 5265'. Bottom marker set at 4254'. Top marker set at 3457'. Cemented with 650 sacks Pecos Valley Lite, 4#/sack D-42, 1#/sack D-44, 2/10% D-65, 3/10% D-167, .2% D-46 and .15% D-13 (yield 1.42, weight 13.0). PD 2:00 AM 11-7-2001. Bumped plug to 1320 psi for 1 minute. WOC. Released rig at 6:00 AM 11-7-2001. NOTE: Notified OCD-Artesia answering service of operations.

Waiting on completion unit.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Operations Technician DATE Nov. 9, 2001

TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY TIM W. GUM
DISTRICT II SUPERVISOR

NOV 16 2001

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: