

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

# OIL CONSERVATION DIVISION

P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO.  
30-005-63336

5. Indicate Type of Lease  
STATE ☒ REF ☐

6. State Oil & Gas Lease No.  
LG-0567

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM G-101) FOR SUCH PROPOSALS.)

1. Type of Well:  
OIL WELL ☐ GAS WELL ☒ OTHER ☐

2. Name of Operator  
YATES PETROLEUM CORPORATION

3. Address of Operator  
105 South 4th St., Artesia, NM 88210

4. Well Location  
Unit Letter D : 660 Feet From The North Line and 660 Feet From The West Line  
Section 36 Township 5S Range 24E NMPM Chaves County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)  
3887' GR

7. Lease Name or Unit Agreement Name  
Grynberg LZ State

8. Well No.  
8

9. Pool name or Wildcat  
Wildcat Precambrian

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>		CASING TEST AND CEMENT JOB <input type="checkbox"/>	
OTHER: <input type="checkbox"/>		OTHER: Production casing & cement <input checked="" type="checkbox"/>	

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 5300'. Reached TD at 10:15 PM 9-15-2001. Ran 124 joints of 4-1/2" 11.6# casing as follows: 57 joints of 4-1/2" 11.6# N-80 sandblasted (2383.15') and 67 joints of 4-1/2" 11.6# N-80 varnished (2900.91') (Total 5284.06') of casing set at 5300'. Float shoe set at 5300'. Float collar set at 5257'. Bottom marker set at 4172'. Top marker set at 2923'. Cemented with 600 sacks Pecos Valley Lite, 4#/sack D-42, 1#/sack D-44, 2/10% D-65, 3/10% D-167, .2% D-45 and .15% D-13 (yield 1.42, weight 13.0). PD 9:00 PM 9-17-2001. Bumped plug to 1900 psi for 4 minutes, OK. WOC. Released rig at 1:00 AM 9-18-2001.

NOTE: Notified Phil Hawkins w/OCD-Artesia of operations.

Waiting on completion unit.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Operations Technician DATE Nov. 9, 2001  
TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-147

(This space for State Use)

ORIGINAL SIGNED BY TIM W. GUM  
DISTRICT II SUPERVISOR

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE NOV 16 2001

CONDITIONS OF APPROVAL, IF ANY: