( <b>1</b> ) ) ) ) ) ) ) ) ) ) ) ) ) ) ) ) ) ) )					
(August 1999)		ED STATES			FORM APPROVED
		F LAND MANAGEME			OMB No. 1004-0135
			<b>A</b> 1	Sour 5 Leas	Expires November 30, 2000
		S AND REPORTS ON		Cons.	
ĩ	Do not use this form for bandoned well. Use Fo	or proposals to drill or t form 3160-3 (APD) for su	o re-enter an IN.IVI. L	IV-Distan	8305
			ich propo <b>4aB01</b> W. G	rand Aver	TUC lottee or Tribe Name
			Artesia,	NM 8821	0
				7. If Ur	hit or CA/Agreement, Name and/or No.
SOBWI	T IN TRIPLICATE -	Other Instructions	on reverse side		
1. Type of Well Oil Well			· · · · · · · · · · · · · · · · · · ·	8. Weil	Name and No.
				Binni	on TT Federal #7
2. Name of Operator Yates Petroleum Corporation					Well No.
					5-63350
105 S. 4th Street - Artesia. NM 88210 505-748-1471				10. Fiel	d and Pool, or Exploratory Area
4. Location of Well (Footage, Se	cription)			at Precambrian	
660 FNL and 660 FEL Sec	ction 24 T7S R25E				inty or Parish, State
12. CHECK A	PPROPRIATE BOX/F	S) TO INDICATE NAT	URE OF NOTICE, REPO		es County, NM
TYPE OF SUMISSION			TYPE OF ACTION	RT, OR OTHER	
Notice of Intent	Acidize		Production (Start/Resume		
X Subsequent Report	Alter Casing	Fracture Treat	_		
Final Abandonment Notice			Reclamation	Well Inte	egrity
	Casing Repair	New Construction	Recomplete	X Other set pro	duction casing
	Change Plans	Plug and Abandon	Temporarily Abandon		
or provide the Bond No. on file with completion or recompletion in a ne reclamation, have been completed	Convert to Injection Operation (clearly state all pertine tally, give subsurface locations ar BLWBIA. Required subsequent w interval, a Form 3160-4 shall b , and the operator has determined	Plug Back ent details, including estimated st nd measured and true vertical de t reports shall be filed within 30 d e filed once testing has been con d that the site is ready for final in	Water Disposal arting date of any proposed work and pths of all pertinent markers and zone ays following completion of the involv	s. Attach the Bond und	der which the work will be performed
completion or recompletion in a ne reclamation, have been completed 7/4/01 - Ran 122 jts. (5158 52 jts. 4-1/2" 11.6# N-80 S 70 jts. 4-1/2" 11.6# N-80 N Regular guide shoe set at	Convert to Injection Operation (clearly state all pertine tally, give subsurface locations ar h BLM/BIA. Required subsequent w interval, a Form 3160-4 shall b , and the operator has determined 8.4') casing set at 5150' a B (2181.60') MV (2976.80') 5150'. Float collar set at ecos Valley Lite + 4 pps I plug to 1900 psi for 4 mi Artesia OCD before setti	Plug Back ent details, including estimated st nd measured and true vertical de t reports shall be filed within 30 d be filed once testing has been could d that the site is ready for final int as follows: 5107.17'. Bottom market D42 + 1 pps D44 + .2% [ ins., held OK	Water Disposal arting date of any proposed work and pths of all pertinent markers and zone ays following completion of the involv mpleted. Final Abandonment Notices specifion.)	<li>s. Attach the Bond unc ed operations. If the op shall be filed only after</li>	der which the work will be performed perations results in a multiple all requirements, including
or provide the Bond No. on file with completion or recompletion in a ne reclamation, have been completed 7/4/01 - Ran 122 jts. (5156 52 jts. 4-1/2" 11.6# N-80 S 70 jts. 4-1/2" 11.6# N-80 M Regular guide shoe set at Cemented with 550 sxs Pe PD at 12:15 PM. Bumped Notified Phil Hawkins with Rig released at 4:15 PM 7.	Convert to Injection Operation (clearly state all pertine tally, give subsurface locations ar n BLM/BIA. Required subsequent winterval, a Form 3160-4 shall b , and the operator has determined 8.4') casing set at 5150' a SB (2181.60') AV (2976.80') 5150'. Float collar set at acos Valley Lite + 4 pps [ 1 plug to 1900 psi for 4 mi Artesia OCD before setti /4/01.	Plug Back ent details, including estimated st nd measured and true vertical de t reports shall be filed within 30 d be filed once testing has been could d that the site is ready for final int as follows: 5107.17'. Bottom market D42 + 1 pps D44 + .2% [ ins., held OK	Water Disposal arting date of any proposed work and pths of all pertinent markers and zone ays following completion of the involv mpleted. Final Abandonment Notices specifion.)	<li>s. Attach the Bond unc ed operations. If the op shall be filed only after</li>	der which the work will be performed perations results in a multiple all requirements, including
or provide the Bond No. on file with completion or recompletion in a ne reclamation, have been completed 7/4/01 - Ran 122 jts. (5158 52 jts. 4-1/2" 11.6# N-80 S 70 jts. 4-1/2" 11.6# N-80 N Regular guide shoe set at Cemented with 550 sxs Pe PD at 12:15 PM. Bumped Notified Phil Hawkins with	Convert to Injection Operation (clearly state all pertine tally, give subsurface locations ar n BLM/BIA. Required subsequent winterval, a Form 3160-4 shall b , and the operator has determined 8.4') casing set at 5150' a SB (2181.60') AV (2976.80') 5150'. Float collar set at acos Valley Lite + 4 pps [ 1 plug to 1900 psi for 4 mi Artesia OCD before setti /4/01.	Plug Back ent details, including estimated st nd measured and true vertical de t reports shall be filed within 30 d be filed once testing has been could d that the site is ready for final int as follows: 5107.17'. Bottom market D42 + 1 pps D44 + .2% [ ins., held OK	Water Disposal arting date of any proposed work and pths of all pertinent markers and zone ays following completion of the involv npieted. Final Abandonment Notices specition.) er set at 4070.21'. 065 + .3% D167 + .2% D46 -	<li>s. Attach the Bond unc ed operations. If the op shall be filed only after</li>	der which the work will be performed perations results in a multiple all requirements, including
or provide the Bond No. on file with completion or recompletion in a ne reclamation, have been completed 7/4/01 - Ran 122 jts. (5156 52 jts. 4-1/2" 11.6# N-80 S 70 jts. 4-1/2" 11.6# N-80 M Regular guide shoe set at Cemented with 550 sxs Pe PD at 12:15 PM. Bumped Notified Phil Hawkins with Rig released at 4:15 PM 7, I hereby certify that the foregoing is Name ( <i>Printed/Typed</i> ) Susan Herpin	Convert to Injection Operation (clearly state all pertine tally, give subsurface locations ar n BLM/BIA. Required subsequent winterval, a Form 3160-4 shall b , and the operator has determined 8.4') casing set at 5150' a SB (2181.60') AV (2976.80') 5150'. Float collar set at acos Valley Lite + 4 pps [ 1 plug to 1900 psi for 4 mi Artesia OCD before setti /4/01.	Plug Back ent details, including estimated st nd measured and true vertical de t reports shall be filed within 30 d be filed once testing has been could d that the site is ready for final int as follows: 5107.17'. Bottom market D42 + 1 pps D44 + .2% [ ins., held OK	Water Disposal arting date of any proposed work and pths of all pertinent markers and zone ays following completion of the involv npieted. Final Abandonment Notices specition.) er set at 4070.21'. 065 + .3% D167 + .2% D46 -	s. Attach the Bond und ed operations. If the op shall be filed only after	der which the work will be performed perations results in a multiple all requirements, including
or provide the Bond No. on file with completion or recompletion in a ne reclamation, have been completed 7/4/01 - Ran 122 jts. (5158 52 jts. 4-1/2" 11.6# N-80 S 70 jts. 4-1/2" 11.6# N-80 N Regular guide shoe set at Cemented with 550 sxs Pe PD at 12:15 PM. Bumped Notified Phil Hawkins with Rig released at 4:15 PM 7.	Convert to Injection Operation (clearly state all pertine tally, give subsurface locations ar n BLM/BIA. Required subsequent winterval, a Form 3160-4 shall b , and the operator has determined 8.4') casing set at 5150' a SB (2181.60') AV (2976.80') 5150'. Float collar set at acos Valley Lite + 4 pps [ 1 plug to 1900 psi for 4 mi Artesia OCD before setti /4/01.	Plug Back ent details, including estimated st nd measured and true vertical de t reports shall be filed within 30 d be filed once testing has been could d that the site is ready for final int as follows: 5107.17'. Bottom market D42 + 1 pps D44 + .2% [ ins., held OK	Water Disposal arting date of any proposed work and pths of all pertinent markers and zone ays following completion of the involv mpleted. Final Abandonment Notices specition.) er set at 4070.21'. P65 + .3% D167 + .2% D46 - Title Engineering Tecl Date	s. Attach the Bond und ed operations. If the op shall be filed only after • .15% D13 (yld 1	der which the work will be performed perations results in a multiple all requirements, including
or provide the Bond No. on file with completion or recompletion in a ne reclamation, have been completed 7/4/01 - Ran 122 jts. (5156 52 jts. 4-1/2" 11.6# N-80 S 70 jts. 4-1/2" 11.6# N-80 M Regular guide shoe set at Cemented with 550 sxs Pe PD at 12:15 PM. Bumped Notified Phil Hawkins with Rig released at 4:15 PM 7, I hereby certify that the foregoing is Name ( <i>Printed/Typed</i> ) Susan Herpin	Convert to Injection Operation (clearly state all pertine tally, give subsurface locations ar n BLM/BIA. Required subsequent winterval, a Form 3160-4 shall b , and the operator has determined 8.4') casing set at 5150' a SB (2181.60') AV (2976.80') 5150'. Float collar set at accos Valley Lite + 4 pps I Plug to 1900 psi for 4 mi Artesia OCD before setti /4/01.	Plug Back ent details, including estimated st and measured and true vertical de treports shall be filed within 30 d be filed once testing has been cord d that the site is ready for final in- as follows: 5107.17'. Bottom market 042 + 1 pps D44 + .2% D ins., held OK. ng pipe.	Water Disposal arting date of any proposed work and pths of all pertinent markers and zone ays following completion of the involv mpleted. Final Abandonment Notices specifion.) er set at 4070.21'. 165 + .3% D167 + .2% D46 - Title Engineering Tect Date Cutubar 3.20	s. Attach the Bond und ed operations. If the op shall be filed only after • .15% D13 (yild 1 • .15% D13 (yild 1	der which the work will be performed perations results in a multiple all requirements, including
or provide the Bond No. on file with completion or recompletion in a ne reclamation, have been completed 7/4/01 - Ran 122 jts. (5158 52 jts. 4-1/2" 11.6# N-80 S 70 jts. 4-1/2" 11.6# N-80 N Regular guide shoe set at Cemented with 550 sxs Pe PD at 12:15 PM. Bumped Notified Phil Hawkins with Rig released at 4:15 PM 7.	Convert to Injection Operation (clearly state all pertine tally, give subsurface locations ar n BLM/BIA. Required subsequent winterval, a Form 3160-4 shall b , and the operator has determined 8.4') casing set at 5150' a SB (2181.60') AV (2976.80') 5150'. Float collar set at accos Valley Lite + 4 pps I Plug to 1900 psi for 4 mi Artesia OCD before setti /4/01.	Plug Back ent details, including estimated st and measured and true vertical de treports shall be filed within 30 d be filed once testing has been cord d that the site is ready for final in- as follows: 5107.17'. Bottom market 042 + 1 pps D44 + .2% D ins., held OK. ng pipe.	Water Disposal arting date of any proposed work and pths of all pertinent markers and zone ays following completion of the involv mpleted. Final Abandonment Notices specition.) er set at 4070.21'. P65 + .3% D167 + .2% D46 - Title Engineering Tecl Date	s. Attach the Bond und ed operations. If the op shall be filed only after • .15% D13 (yild 1 • .15% D13 (yild 1	der which the work will be performed perations results in a multiple all requirements, including
or provide the Bond No. on file with completion or recompletion in a ne reclamation, have been completed 7/4/01 - Ran 122 jts. (5158 52 jts. 4-1/2" 11.6# N-80 S 70 jts. 4-1/2" 11.6# N-80 N Regular guide shoe set at Cemented with 550 sxs Pe PD at 12:15 PM. Bumped Notified Phil Hawkins with Rig released at 4:15 PM 7.	Convert to Injection Operation (clearly state all pertine tally, give subsurface locations ar n BLM/BIA. Required subsequent winterval, a Form 3160-4 shall b , and the operator has determined 8.4') casing set at 5150' a SB (2181.60') AV (2976.80') 5150'. Float collar set at accos Valley Lite + 4 pps I Plug to 1900 psi for 4 mi Artesia OCD before setti /4/01.	Plug Back ent details, including estimated st and measured and true vertical de treports shall be filed within 30 d be filed once testing has been cord d that the site is ready for final in- as follows: 5107.17'. Bottom market 042 + 1 pps D44 + .2% D ins., held OK. ng pipe.	Water Disposal arting date of any proposed work and pths of all pertinent markers and zone ays following completion of the involv mpleted. Final Abandonment Notices specifion.) er set at 4070.21'. 165 + .3% D167 + .2% D46 - Title Engineering Tect Date Cutubar 3.20	s. Attach the Bond und ed operations. If the op shall be filed only after • .15% D13 (yild 1 • .15% D13 (yild 1	der which the work will be performed perations results in a multiple all requirements, including
or provide the Bond No. on file with completion or recompletion in a ne reclamation, have been completed 7/4/01 - Ran 122 jts. (5156 52 jts. 4-1/2" 11.6# N-80 S 70 jts. 4-1/2" 11.6# N-80 N Regular guide shoe set at Cemented with 550 sxs Pe PD at 12:15 PM. Bumped Notified Phil Hawkins with Rig released at 4:15 PM 7.	Convert to Injection Coperation (clearly state all pertine tally, give subsurface locations ar bBLW/BIA. Required subsequeni winterval, a Form 3160-4 shall b , and the operator has determined B.4') casing set at 5150' a SB (2181.60') AV (2976.80') 5150'. Float collar set at ecos Valley Lite + 4 pps [ plug to 1900 psi for 4 mi Artesia OCD before setti /4/01	Plug Back ent details, including estimated st and measured and true vertical de treports shall be filed within 30 d be filed once testing has been cord d that the site is ready for final in- as follows: 55107.17'. Bottom marke 042 + 1 pps D44 + .2% D ins., held OK. ng pipe.	Water Disposal arting date of any proposed work and pths of all pertinent markers and zone ays following completion of the involv mpleted. Final Abandonment Notices specition.) er set at 4070.21'. 165 + .3% D167 + .2% D46 - Title Engineering Tech Date Cutubar 3 20 RAL OR STATE OFFICE Title	s. Attach the Bond und ed operations. If the op shall be filed only after • .15% D13 (yild 1 • .15% D13 (yild 1	der which the work will be performed perations results in a multiple all requirements, including .42, wt 13.)
or provide the Bond No. on file with completion or recompletion in a ne reclamation, have been completed 7/4/01 - Ran 122 jts. (5158 52 jts. 4-1/2" 11.6# N-80 S 70 jts. 4-1/2" 11.6# N-80 N Regular guide shoe set at Cemented with 550 sxs Pe PD at 12:15 PM. Bumped Notified Phil Hawkins with Rig released at 4:15 PM 7. I hereby certify that the foregoing is Name (Printed/Typed) Signature	Convert to Injection Coperation (clearly state all pertine tally, give subsurface locations ar bBLM/BIA. Required subsequent winterval, a Form 3160-4 shail b , and the operator has determined B.4') casing set at 5150' a SB (2181.60') AV (2976.80') 5150'. Float collar set at ecos Valley Lite + 4 pps [ plug to 1900 psi for 4 mi Artesia OCD before setti /4/01. THIS S tached. Approval of this notice of e tifle to those rights in the subsequent	Plug Back Plug Back Plug Back and measured and true vertical de treports shall be filed within 30 d be filed once testing has been con- d that the site is ready for final in- as follows: 5107.17'. Bottom marke D42 + 1 pps D44 + .2% D ins., held OK. ng pipe. SPACE FOR FEDEF	Water Disposal arting date of any proposed work and pths of all pertinent markers and zone ays following completion of the involv mpleted. Final Abandonment Notices specifion.) er set at 4070.21'. 165 + .3% D167 + .2% D46 - Title Engineering Tech Date CHUBL 3.20 RAL OR STATE OFFIC	s. Attach the Bond und ed operations. If the op shall be filed only after • .15% D13 (yild 1 • .15% D13 (yild 1	der which the work will be performed perations results in a multiple all requirements, including .42, wt 13.)
or provide the Bond No. on file with completion or recompletion in a ne reclamation, have been completed 7/4/01 - Ran 122 jts. (5154 52 jts. 4-1/2" 11.6# N-80 S 70 jts. 4-1/2" 11.6# N-80 N Regular guide shoe set at Cemented with 550 sxs Pe PD at 12:15 PM. Bumped Notified Phil Hawkins with Rig released at 4:15 PM 7. I hereby certify that the foregoing is Name ( <i>Pinted/Typed</i> ) Susan Herpin Signature 2007 A 2007 A 2007 A Approved by Conditions of approval. if any, are a the applicant to conduct operations the	Convert to Injection Deperation (clearly state all pertine tally, give subsurface locations an BLM/BIA. Required subsequent winterval, a Form 3160-4 shall b , and the operator has determined B.4') casing set at 5150' a SB (2181.60') AV (2976.80') 5150'. Float collar set at accos Valley Lite + 4 pps [ plug to 1900 psi for 4 mi Artesia OCD before setti /4/01.  THIS S ttached. Approval of this notice o e title to those rights in the subjection te 43 U.S.C. Section 1212, make	Plug Back ent details, including estimated st nd measured and true vertical de treports shall be filed within 30 d be filed once testing has been cord d that the site is ready for final in- its follows: 5107.17'. Bottom marked D42 + 1 pps D44 + .2% D ins., held OK. ng pipe. <b>SPACE FOR FEDER</b> does not warrant or certify that t lease which would entitle the t a crime for any person knowing	Water Disposal arting date of any proposed work and pths of all pertinent markers and zone ays following completion of the involv mpleted. Final Abandonment Notices specition.) er set at 4070.21'. 165 + .3% D167 + .2% D46 - Title Engineering Tech Date Cutubar 3 20 RAL OR STATE OFFICE Title	s. Attach the Bond und ed operations. If the op shall be filed only after 	der which the work will be performed perations results in a multiple all requirements, including .42, wt 13.)