

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.
30-005-63356

5. Indicate Type of Lease
STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☐ GAS WELL ☒ OTHER

2. Name of Operator
YATES PETROLEUM CORPORATION /

3. Address of Operator
105 South 4th St., Artesia, NM 88210

4. Well Location
Unit Letter I : 1880 Feet From The South Line and 660 Feet From The East Line

Section 23 Township 6S Range 25E NMPM Chaves County
10. Elevation (Show whether DF, RKB, RT, GR, etc.)
3778' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: <u>Production casing & cement</u> <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.
TD 5430'. Reached TD at 7:15 AM 7-24-2001. Ran 129 joints of 4-1/2" 11.6# N-80 casing as follows: 56 joints of 4-1/2" 11.6# N-80 sandblasted (2338.63') and 73 joints of 4-1/2" 11.6# N-80 varnished (3087.37') (Total feet 5426') of casing set at 5426'. Float shoe set at 5426'. Float collar set at 5384'. Bottom marker set at 4298'. Top marker set at 3087'. Cemented with 650 sacks Pecos Valley Lite, 4#/sack D-42, 1#/sack D-44, 2/10% D-65, 3/10% D-167, .2% D-46 and .15% D-13 (yield 1.42, weight 13.0). PD 10:00 AM 7-26-2001. Bumped plug to 1600 psi for 4 minutes, OK. WOC. Released rig at 2:00 PM 7-26-2001.
NOTE: Notified Phil Hawkins w/OCD-Artesia of operations.

Waiting on completion unit.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Operations Technician DATE Oct. 30, 2001
TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY TIM W. GUM
DISTRICT II SUPERVISOR

NOV 16 2001

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: