

YATES PETROLEUM CORPORATION
Sacra SA Com #12
Section 23-T6S-R25E
Chaves County, New Mexico

SUNDRY NOTICE CONTINUED:

8-28-2001 - Spotted 500 gallons of 7-1/2% iron control HCL acid over perforations 3708-3979' (Abo). TOOH with tubing. Nippled down BOP.

8-29-2001 - Nippled up frac valve.

8-30-2001 - Frac'd perforations 3708-3979' (Abo) (down 4-1/2" casing) with 146000 gallons 65Q foam and 313000# 16-30 Brady sand. Spearheaded 2000 gallons of 7-1/2% iron control HCL acid ahead of frac. Shut well in 2 hours. Opened well up and began flowing back frac.

8-31-2001 - Flowed back frac. Shut well in.


9-1-4-2001 - Bled well down. Flow tested. Pumped 50 bbls KCL water down casing. TIH with tubing to 4200'. Pulled up and set seating nipple at 3670'. Nippled down BOP. Flow tested. Shut well in.

9-5-2001 - Flow tested. Shut well in.

9-6-2001 - Flow tested. Shut well in.

9-7-2001 - Flow tested. Shut well in.

9-8-10-2001 - Released well to production department



Rusty Klein
Operations Technician
October 30, 2001