

Submit 3 Copies To Appropriate District  
Office  
District I  
1625 N. French Dr., Hobbs, NM 88240  
District II  
811 South First, Artesia, NM 88210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
1220 S. St. Francis Dr., Santa Fe, NM  
87505

State of New Mexico  
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

Form C-103  
Revised March 25, 1999

WELL API NO.

30-005-63360

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

VA-2059

7. Lease Name or Unit Agreement Name:

Keno AWK State

7. Well No.

#1

8. Pool name or Wildcat

Wildcat PreCambrian

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☒ Other ☐

2. Name of Operator

Yates Petroleum Corporation

3. Address of Operator

105 S. 4th Street Artesia, NM 88210

4. Well Location

Unit Letter B : 660 feet from the North line and 1980 feet from the East line

Section 4 Township 10S Range 26E NMPM Chaves County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

3790' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☒

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

4/24/01 - Spud with rathole machine at 9:00 AM. Set 40' of 16" conductor pipe cemented to surface.

5/4/01 - Resumed drilling with 12-1/4" hole with rotary tool at 4:30 AM.

5/6/01 - TD surface hole at 1108' at 2:00 AM. Ran 26 jts. (1109.61') 8-5/8" 24# J-55 casing set at 1108'. Texas Pattern guide shoe set at 1108'. Insert float set at 1064.95'. Cemented with 450 sxs 35:65 Poz C + 6% D20 + 2% S1 + 1/8 pps D130 (yld 1.99, wt 12.6). Tailed in with 200 sxs C + 2% CaCl2 (yld 1.32, wt 14.8). PD at 12:45 PM. Bumped plug to 567#, held OK. Circ 39 sxs. WOC. Notified Phil Hawkins with Artesia OCD of intended operations on 5/5/01.

5/7/01 - Drilled out at 7:00 AM. WOC 18 hrs. 15 mins. Reduced hole to 7-7/8" and resumed drilling.

5/8 - 5/21/01 - Drilling.

5/21/01 - Reached TD at 6300' at 12:45 PM.

5/22/01 - Run open hole logs and sidewall cores. Logger's TD 6285'.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Susan Herpin TITLE Engineering Technician DATE October 4, 2001

Type or print name Susan Herpin

Telephone No. 505-748-1471

(This space for State use)

APPROVED BY TIM W. GUM ORIGINAL SIGNED BY TIM W. GUM

DISTRICT II SUPERVISOR

DATE OCT 07 2001

Conditions of approval, if any: