			CISE		
Submit 3 Copies To Appropriate District State of New Mexico			-60	Form C-103	
Office District I	Energy, Minerals and Nat			Revised March 25, 1999	
1625 N. French Dr., Hobbs, NM 88240			WELL API NO. 30-005-63360		
District II S11 South First, Artesia, NM 88210	OIL CONSERVATION DIVISION			er.	
District III 1000 Rio Brazos Rd., Aztec, NM 87410	Pio Brazos P.d. Agree NM 97410			of Lease	
District IV Santa Fe, NM 8/505			6. State Oil & G		
1220 S. St. Francis Dr., Santa Fe, NM 87505			VA-2059		
SUNDRY NOTICES AND REPORTS ON WELLS			7. Lease Name or	Unit Agreement Name:	
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH			V ANNV CL-	.1.	
PROPOSALS.)			Keno AWK Sto	ire	
1. Type of Well: Oil Well Gas Well X	Other \	66/3920			
2. Name of Operator	Other	A	7. Well No.		
Yates Petroleum Corporation			#1		
3. Address of Operator	:	RECENTED A	8. Pool name or		
105 S. 4 <sup>th</sup> Street Artes	ia, NM 88210	RECEIVESIA TO ARTESIA	Foor Ranc	h Wolfcamp	
4. Well Location		30			
Unit Letter B: 660	feet from the North	line and	feet from the <b>Ea</b> :	st line	
		0.5			
Section 4	Township 10S Range		MPM Chave	<b>S</b> County	
10. Elevation (Show whether DR, RKB, RT, GR, etc.)  3790' GR					
11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data					
NOTICE OF IN			SEQUENT REI		
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WOR	EMEDIAL WORK ALTERING CASING X		
TEMPORARILY ABANDON	CHANGE PLANS	COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT			
PULL OR ALTER CASING	MULTIPLE COMPLETION	CASING TEST AND CEMENT JOB			
OTHER:	OTHER: perforate, acidize				
Describe proposed or completed or					
starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or					
recompilation. 6/11/01 – TIH with bit and scraper to 6180'. Tagged up.					
6/12/01 - Run GR/CBL/CCL. TOC 3600'.					
Perforate Ordocvician 5892-5906', 30 holes, 5916-5924', 18 holes and 5930-5940', 22 holes, .42" holes.					
6/13/01 - Spot 100 gals 20% IC HCL. Break perfs. Rig up swab.					
6/19/01 – Squeeze Ordovician perfs. Set retainer at 5828°. Squeeze perfs 5892-5940' with 200 sxs Class C + fluid loss. Squeezed to 2000#. Reversed 98 sxs to pit.					
Perforate Wolfcamp Spear Zone 5414-5424', 22 holes, .42".					
6/21/01 – Spot 50 gals 15% IC HCL. Break perfs. Acidize with 1000 gals 15% IC HCL + ball sealers. Rig up swab.					
6/25/01 - Rig down and move	e off. Turn well to production	n.			
I hereby certify that the information above is true and complete to the best of my knowledge and belief.					
SIGNATURE AND ME	•				
SIGNATURE And MI	TITLE TITLE	<u>Engineering</u>	<b>Technician</b> DA	ATE <u>October 4, 2001</u>	
Type or print name Susan Herpin Telephone No. 505-748-147					
(This space for State use)	ORIGINAL SIGNED BY TIM	W. GUM		286 as a	
APPPROVED BY	DISTRICT II SUPERVISOR	<del>-</del> -		DATE_ OCT 0 7 200	
Conditions of approval if any	IIILE			DAIL	