

Submit 3 Copies To Appropriate District Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 South First, Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

CIS
of

Form C-103
Revised March 25, 1999

WELL API NO.

30-005-63364

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

V-5649

7. Lease Name or Unit Agreement Name:

Quiniela AXQ State

7. Well No.

2

8. Pool name or Wildcat

Undesignated Foor Ranch
Pre-Permian

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☒ Other ☐

2. Name of Operator

Yates Petroleum Corporation

3. Address of Operator

105 S. 4th Street Artesia, NM 88210

4. Well Location

Unit Letter **G** : **1980** feet from the **North** line and **1980** feet from the **East** line

Section **5** Township **10S** Range **26E** NMPM **Chaves** County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

3777' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: Perforate ☒

Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

5/22/02 - Bled down tubing. Loaded tubing. Nippled up 3OP and released packer. TOH. TIH with bit and collars. Tagged sand at 5440'. Circulate out 140' sand. Drilled out CIBP at 5580'. TIH and tagged sand at 5859'. Circulate down to PBTD 5930'. Pulled up above perms.

5/23/02 - TOH with bit and collars. Perforate Silurian from 5770'-5790', 5794'-5798', 5804'-5808', 5812'-5816'. 4 JSPF, 128 holes, .42" hole. TIH with packer with knock out plug. Set at 5750'. Drop bar to knock out plug.

5/24/02 - Acidized perms 5770'-5816' with 3200 gals 20% IC acid and ball sealers.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Tina Huerta

TITLE **Regulatory Compliance Supervisor**

DATE **May 31, 2002**

Type or print name

Tina Huerta

Telephone No. **505-748-1471**

(This space for State use)

APPROVED BY

[Signature]

ORIGINAL SIGNED BY TIM W. GUM
DISTRICT II SUPERVISOR

Conditions of approval, if any

DATE

JUN 05 2002