		25272	1 c M
			Çons.
Form 3160-, (Avgust 1999)	UNITED STATES DEPARTMENT OF THE INTERIOR_	N.M. D	V-Dist. 2FORM APPROVED
	BUREAU OF LAND MANAGEMENT		and Avenue Necember 30, 2000
SUNDR	IY NOTICES AND REPORTS ON W	AIGSIG.	NM 188210 0. NM-10588
Do not use the abandoned we	nis form for proposals to drill or to r ell. Use Form 3160-3 (APD) för such p	e-enter an S proposals, V	6. If Indian, Allottee or Tribe Name
SUBMIT IN TR	IPLICATE - Other instructions on	reverse side	7. If Unit or CA/Agreement, Name and/or No.
1. Type of Well		*	8. Well Name and No.
Oil Well X Gas Well Z. Name of Operator			George QJ Federal #10
Yates Petroleum (Corporation -		9. API Well No.
3a. Address		No. (include area code)	30-005-63368
105 S. 4th St Artesia, NM 88210 505-748-1471 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 505-748-1471		10. Field and Pool, or Exploratory Area Undesignated Cisco	
	FWL of Section 26-T6S-R25E	(Unit N, SESW)	11. County or Parish, State
			Chaves Co., NM
12. CHECK AI	PROPRIATE BOX(ES) TO INDICATI		REPORT, OR OTHER DATA
TYPE OF SUBMISSION		TYPE OF ACTION	
	Acidize Deepen	Production (Sta	
Notice of Intent	Alter Casing Fracture 1		🔲 Well Integrity 🖾 _{Other} Spud, conductor
Subsequent Report	Casing Repair New Con Change Plans Plug and		
Final Abandonment Notice	Convert to Injection Plug Back		
If the proposal is to deepen dire Attach the Bond under which t following completion of the inv testing has been completed. F determined that the site is ready	cctionally or recomplete horizontally, give subsur he work will be performed or provide the Bond volved operations. If the operation results in a mi inal Abandonment Notices shall be filed only aft of final inspection.)	face locations and measured and the No. on file with BLM/BIA. Requilible completion or recompletion er all requirements, including rec	any proposed work and approximate duration thereof. rue vertical depths of all pertinent markers and zones, nired subsequent reports shall be filed within 30 days in a new interval, a Form 3160-4 shall be filed once lamation, have been completed, and the operator has Drilled to 40'. Set 40'
of 16" conductor p spud. Resumed dra	e with rat hole machine at pipe. Cemented to surface. illing a 14-3/4" hole with p w/BLM-Roswell of resuming	NOTE: Notified S rotary tools at 3:0	Stan Mayo w/BLM-Roswell of
set at 905'. 1-Te Cemented with 200 and 400 sacks Poz Tailed in with 200 2001. Bumped plug hours. Ran Tempes at 195'. Spotted Ran 1". Tagged co	exas Pattern notched guide sacks "H", 10#/sack gilson C (65-35-6), 2% CaCl2 and O sacks "C" and 2% CaCl2 (y g to 1068 psi, float did no rature Survey and found top 50 sacks Class C and 3% Ca ement at 175'. Spotted 50	shoe set at 905'. ite, 1/4#/sack poly 1/4#/sack polyflake ield 1.32, weight i t hold. Cement did of cement at 200' Cl2. PD 12:45 AM i sacks Class C and i	yflake, 2% CaCl2, 10% gyp e (yield 1.99, weight 12.6). 14.8). PD 4:20 PM 7-15- 1 not circulate. WOC 6 . Ran 1". Tagged cement 7-16-2001. WOC 2 hours.
14. I hereby certify that the foregoi Name (Printed/Typed)	ng is true and correct	CONTINUED ON NI	
Rusty Klein	_	Title Operations To	echnician
	VI.		
Signature Misley	- Ulu	Date August 15, 20	
ACCEPTED	FOR RECORDER	AL OR STATE OFFICE US	
Approved by) DAVID H. GLASS	Title	Date
	Authched Approval of this notice does not war at or equitable title to those rights in the subject conduct operations thereon.		
Title 18 U.S.C. Section 10(DAMD States any false, fictitipus presented	Bir 46 LASS Section 1212, make it a crime for a BM ENGINEE Representations as to any matter	any person knowingly and willfull within its jurisdiction.	y to make to any department or agency of the United

YATES PETROLEUM CORPORATION George QJ Federal #10 Section 26-T6S-R25E Chaves County, New Mexico

SUNDRY NOTICE CONTINUED:

CaCl2. PD 6:00 AM 7-16-2001. WOC 2 hours. Ran 1". Tagged cement at 170'. Spotted 50 sacks Class C and 3% CaCl2. PD 8:00 AM 7-16-2001. WOC 2 hours. Ran 1". Tagged cement at 170'. Spotted 125 sacks Class C and 3% CaCl2. PD 10:00 AM 7-16-2001. WOC 2 hours. Ran 1". Tagged cement at 100'. Spotted 65 sacks Class C and 2% CaCl2. PD 12:00 noon 7-16-2001. Circulated 10 sacks. WOC. Nippled up and tested to 1000 psi for 10 minutes, OK. Drilled out at 10:00 PM 7-16-2001. WOC 29 hours and 40 minutes. Reduced hole to 11". Resumed drilling. NOTE: Casing got stuck at 905'. Received permission from Stan Mayo w/BLM-Roswell to cement casing at 905'. Stan Mayo witnessed job.

Rusty Klein

Operations Technician August 15, 2001

ACCEPTED FOR RECOR	RD
ORIG. SGD.) DAVID R. GL	ASS
DAVID R. GLASS PETROLEUM ENGINEER	