

DISTRICT I
P.O. Box 1980, Hobbs NM 88240
DISTRICT II
P.O. Drawer DD, Artesia NM 88210
DISTRICT III
1000 Rio Brazos Rd., Aztec NM 87410

State of New Mexico
Energy, Minerals and Natural Resources Department

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.
30-005-63370

5. Indicate Type of Lease
State ☒ FEE ☐

7. Lease Name or Unit Agreement Name
Skink "SK" State

8. Well No
#6

9. Pool Name or Wildcat
Pecos Slope ABO

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL ☐ GAS ☐
WELL ☐ WELL ☒ OTHER ☐

2. Name of Operator
Yates Petroleum Corporation

3. Address of Operator
105 South 4th., Artesia, NM 88210

4. Well Location
Unit Letter L : 1980' Feet From The South Line and 1300' Feet From The West Line
Section 36 Township 7S Range 25E NMPM Chaves COUNTY

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
3601' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER Spud & Conductor. resume drlg ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

4/26/01-Building location. Auger air set 40' conductor and cemented. Spud time 11:45 AM
4-25-01. Line pits on 4/26/01. 5/3/01 Resumed drilling at 12:01 am 5-3-01. Notified Phil Hawkins with OCD at 9:00 pm 5-2-01. 5-5-01 TD 927' San Andres. Running casing. Reached TD at 12:15 AM 5-5-01. TOH to run casing. Cut off conductor and rigged up casing crew. Running 11-3/4" casing. 5-6-01 Made 83' in 2-1/2 hours. WOC. Drilled out at 3:30 am 5-6-01. Drilled to 1010'. Detailed Casing Report: Ran 22 joints 11-3/4" 43# H# casing, set at 927'. Cemented with 350 sacks 35:65 C - 2% CaCl2 + 1/8#sx Polyflake (yld 1.99, wt 12.6). Tailed in with 200 sacks C + 2% CaCl2 (yld 1.32, wt 14.8). PD at 8:15 am 5-5-01. Circulated 80 sacks cement. WOC. Drilled out at 3:30 am 5-6-01. WOC 19 hours and 15 mins. Reduced hole to 11" and resumed drilling. Notified Phil Hawkins at OCD at 2:00 am. 5-5-01. 5-8-01 TOH for 7-7/8" bit. Drilling. 5-18-01-Drilled to 5230'. TD at 8:30 PM 5-17-01. 5/20/01-released rig 8:30 PM 5-19-01.

RECEIVED
OCD - ARTESIA

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Erma Vazquez TITLE Drilling Technician DATE 12/18/01
TYPE OR PRINT NAME Erma Vazquez TELEPHONE NO 505-748-1471
(This space for State Use)
APPROVED BY Jim W. Gunn TITLE SUPERVISOR, DISTRICT II DATE DEC 28 2001
CONDITIONS OF APPROVAL IF ANY: