

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO.  
30-005-63372

5. Indicate Type of Lease  
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.  
V-4916

7. Lease Name or Unit Agreement Name

Danna AYN State

8. Well No.  
1

9. Pool name or Wildcat  
Undesignated Wolfcamp

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:  
OIL WELL ☐ GAS WELL ☒ OTHER ☐

2. Name of Operator  
YATES PETROLEUM CORPORATION

3. Address of Operator  
105 South 4th St., Artesia, NM 88210

4. Well Location  
Unit Letter L : 1980 Feet From The South Line and 660 Feet From The West Line

Section 31 Township 10S Range 27E NMPM Chaves County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3710' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐ REMEDIAL WORK ☐ ALTERING CASING ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐ COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐  
PULL OR ALTER CASING ☐ CASING TEST AND CEMENT JOB ☐  
OTHER: ☐ OTHER: Production casing & cement ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 6400'. Reached TD at 3:30 AM 6-26-2001. Ran 152 joints of 4-1/2" 11.6# casing as follows:  
45 joints of 4-1/2" 11.6# N-80 sandblasted (1879.55') and 107 joints of 4-1/2" 11.6# N-80  
varnished (4527.69') (Total 6407.24') of casing set at 6400'. Float shoe set at 6400'.  
Float collar set at 6354'. Bottom marker set at 5360'. Top marker set at 4520'. Cemented  
with 550 sacks of Pecos Valley Lite, 1#/sack D-44, 4#/sack D-24, .2% D-65, .3% D-167, .2%  
D-46 and .15% D-13 (yield 1.42, weight 13.0). PD 8:30 PM 6-27-2001. Bumped plug to 1353  
psi for 2 minutes, OK. WOC. Released rig at 1:30 AM 6-28-2001.

Waiting on completion unit.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Operations Technician DATE Aug. 30, 2001

TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY TIM W. GUM  
DISTRICT II SUPERVISOR

DEC 13 2001

APPROVED BY [Signature] TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY: