-	-		-d51	
Submit 3 Copies To Appropriate District State of New Mexico			<u> </u>	Form C-103
Office District I Energy, Minerals and Natural Resources			40	Revised March 25, 1999
1625 N. French Dr., Hobbs, NM 88240			WELL API NO.	
District II 811 South First, Artesia, NM 88210 OIL CONSERVATION DIVISION			30-005-63373 5. Indicate Type of	of Leace
District III 1220 South St. Francis Dr. 1000 Rio Brazos Rd., Aztec, NM 87410			STATE [FEE
District IV 1220 S. St. Francis Dr., Santa Fe, NM			6. State Oil & G	as Lease No.
87505 SUNDRY NOTICES AND REPORTS ON WELLS			V-4916	TT-14 A
SUNDRY NOTICES AT (DO NOT USE THIS FORM FOR PROPOSALS TO		I G BAC K TO A	/. Lease Name or	Unit Agreement Name:
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH 75 (FORM C-101) FORM C-101) FOR SUCH 75 (FORM C-101) FORM FOR SUCH 75 (FORM C-101) FOR SUCH 75 (FOR			Trey AYR State Com	
1. Type of Well:		92		
Oil Well Gas Well X Oth 2. Name of Operator	er / ශ්		7. Well No.	
Yates Petroleum Corporation		CENECIA	#1	
3. Address of Operator	8. Pool name or			
105 S. 4th Street Artesia, NM 88210			Foor Ranci	ń Wolfcamp
4. Well Location				
The first Bookings				
Unit Letter D: 660	feet from the North	_ line and 660	feet from the	West line
Section 31 Towns	hip 10S Range 27	E NMPN	1 Chaves	County
	Elevation (Show whether DI			Section of the sectio
3737'GR				
	riate Box to Indicate Na			
			SEQUENT REF	ALTERING
PERFORM REMEDIAL WORK PLUG	S AND ABANDON	REMEDIAL WORK	WEDIAL WORK CASING	
TEMPORARILY ABANDON CHANGE PLANS COMMENCE DR			PLUG AND ABANDONMENT	
	PLETION	CASING TEST AN CEMENT JOB		
OTHER:			ement production of	
Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of				
starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.				
6/1/01 – Reached TD at 6960' at 3:30 PM.				
6/2/01 - Run logs. Logger's TD 6956'.				
6/4/01 – Rqn 166 joints (6961.71') casing set at 6960' as follows: 57 joints 5-1/2" 15.5# J-55 SB (2389.02')				
109 joints 5-1/2" 15.5# J-55 MV (4572.69')				
Float shoe set at 6960'. Float collar set at 6915.7'. Bottom marker set at 5915.80'. Top marker set at 4570.98'.				
Cemented with 500 sxs Pecos Valley Lite with 1 pps D44 + 4 pps D24 + .2% D65 + .3% D167 + .2% D46 + .15% D13				
(yld 1.42, wt 13). Plug down at 8:47 AM. Bumped plug to 1580 psi for 3 mins, held OK.				
Rig released at 12:45 PM 6/4/01	19 10 1000 partor 5 mins	, field Ok.		
G				
Thombs and first the information of	is two and complete to the	hogt of my large 1, 1,	ro and haliaf	
I hereby certify that the information above is true and complete to the best of my knowledge and belief.				
SIGNATURE Missing Higher TITLE Engineering Technician DATE January 8, 2002				
Type or print name Susan Herpin			Telephone	No. 505-748-1471
(This space for State 1860)	ICHEN DY TIM W GILL	1		JAN 1 0 2002
DISTRICT I	SIGNED BY TIM W. GUN SUPERVISOR TITLE			
APPPROVED BY	IIILE_	<u> </u>		DATE