APPROVED BY ---

CONDITIONS OF APPROVAL, IF ANY:

State of New Mexico Energy, Minerals and Natural Resources Department

15F	,
PP	Form C-103 Revised 1-1-89

District Office	Ĭ,
DISTRICT I P.O. Box 1980, Hobbs, NM 88240 OIL CONSERVATION DIVISION	WELL API NO.
1.O. DOX 2000	30-005-63377
DISTRICT II Santa Fe, New Mexico 8/504-2088 P.O. Drawer DD, Artesia, NM 88210	5. Indicate Type of Lease STATE X FEE FEE
DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 8741)	6. State Oil & Gas Lease No. LG-5078
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"	7. Lease Name or Unit Agreement Name
(FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL OAS	
WELL X OTHER	Night Owl AFA State Com 8. Well No.
2. Name of Operator YATES PETROLEUM CORPORATION RECURED	8. Well No.
3. Address of Operator	9. Pool name or Wildcat
105 South 4th St., Artesia, NM 88210	Wildcat Cisco
4. Well Location Unit Letter P: 660 Feet From The South Line and 990	Feet From The <u>East</u> Line
22	
Section 22 Township 9S Range 26E [[] 10. Elevation (Show whether DF, RKB, RT, GR, etc.)	NMPM Chaves County
//////////////////////////////////////	
11. Check Appropriate Box to Indicate Nature of Notice, H	Report, or Other Data
NOTICE OF INTENTION TO: SUI	BSEQUENT REPORT OF:
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK	ALTERING CASING
TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLIN	IG OPNS. PLUG AND ABANDONMENT
PULL OR ALTER CASING	
OTHER: Spud, co	onductor, resume drilling, X
12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, incl	casing & cement
work) SEE RULE 1103.	and garden was of surroug any proposed
Spudded a 20" hole with rat hole machine at 6:30 AM 5-12-2 of 16" conductor pipe. Cemented to surface. Resumed drittools at 9:30 AM 5-17-2001.	2001. Drilled to 40'. Set 40' lling a 12-1/4" hole with rotary
TD 1126'. Reached TD at 11:30 AM 5-18-2001. Ran 26 joins of casing set at 1126'. 1-Texas Pattern notched guide she set at 1087'. Cemented with 400 sacks "C" (65-35-6), 1/8 (yield 1.99, weight 12.6). Tailed in with 114 sacks Class weight 14.8). PD 8:30 PM 5-18-2001. Bumped plug to 550# WOC 6 hours. Ran Temperature Survey and found top of cement at 240'. Spotted 190 sacks of Class C Neat. PD 5 10 sacks. WOC. Nippled up and tested to 500 psi for 15 8:45 PM 5-19-200. WOC 24 hours and 15 minutes. Reduced	oe set at 1126'. Insert float #/sack polyflake and 2% CaC12 s C and 2% CaC12 (yield 1.32, , OK. Cement did not circulate. ent at 200'. Ran 1". Tagged :30 AM 6-19-2001. Circulated minutes, OK. Drilled out at
I hereby certify that the information above to the and complete to the best of my knowledge and belief.	m 1 / /
SIGNATURE	Technician July 11, 2001
TYPE OR PRINT NAME Rusty Klein	ТЕЦЕРНОМЕ NO. 505/748—147.
(This space for State Uses ORIGINAL SIGNED BY TIM W. GUM DISTRICT II SUPERVISOR	NOV 12 2801
ATTE	DATE